

185 Watt Hazardous Location LED Light - Magnetic Mount - C1D2 - ATEX - 100 foot Cord w/ EXP Plug

HAL-MB-185LED-CPR-100

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



HAL-MB-185LED-CPR-100 LED Magnetic Mount Light

Lamp Type: LED

LED Light Dimensions: 15.75"L x 15.75"W x 7.28"H

Weight: 45 lbs

Voltage: Universal- 90-305V AC, 50/60Hz

Total Watts: 185W

Total Lumens: 18,500

Luminous Efficacy: 100 Lm/W

LED Lamp Life Expectancy: 100,000+ Hours

Color Temp: 5700K, Cool White (Also available in 4000K and 2700K)

Beam Angle: 120°

Power Factor: ~0.98

Operating Temperature Range: -30°C to +65°C

Housing Material: Die Cast Aluminum

Lens Material: Tempered Glass

Housing Color: Grey

Mounting: Magnetic Shelf with Base Stand

Wiring: 100' 16/3 SOOW Cable

Cord Cap: 5-15, 5-20, or 6-20 Explosion Proof Cord Cap

Ratings

Class I Division 2 Groups A,B,C,D

UL 844

PSE Certified

SAA Certified

Magnetic Shelf with Base Stand

Made in the USA

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)









Options:

HAL-MB-185LED-CPR-100-Cord Cap

Example: HAL-MB-185LED-CPR-100-1523

Cord Cap	
5-15 125V	-1523
5-20 125V	-2023-125V
6-20 250V	-2023-250V

Links (Click on the below items to view):

- [Operations Manual](#)
- [Wiring Diagram \(Online\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)