

## 370 Watt Hazardous Location LED Light Tower - Quadpod Mount - C1D2 - 100 foot Cord w/ EXP Plug

### HAL-QP-2X185LED-CPR-100

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



#### HAL-QP-2X185LED-CPR-100 Light Fixture

**Lamp Type:** LED

**LED Light Dimensions:** 15.75"L x 15.75"W x 7.28"H

**Weight:** 50 lbs

**Voltage:** Universal- 90-305V AC, 50/60Hz

**Total Watts:** 370W

**Total Lumens:** 37,000

**Luminous Efficacy:** 100 Lm/W

**LED Lamp Life Expectancy:** 100,000+ Hours

**Color Temp:** 5700K, Cool White (Also available in 4000K and 2700K)

**Beam Angle:** 120°

**Power Factor:** ~0.98

**Operating Temperature Range:** -30°C to +65°C

**Housing Material:** Die Cast Aluminum

**Lens Material:** Tempered Glass

**Housing Color:** Grey

**Mounting:** 7-12' Adjustable Metal Quadpod

**Wiring:** 100' 16/3 SOOW Cable

**Cord Cap:** 5-15, 5-20, or 6-20 Explosion Proof Cord Cap

#### Ratings

Class I Division 2 Groups A,B,C,D

UL 844

PSE Certified

SAA Certified

7-12' Adjustable Quadpod

Made in the USA

#### Special Orders- Requirements

Contact us for special requirements

**Toll Free:** 1-800-369-6671

**Intl:** 1-903-270-1187

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)



---

## Frequently Asked Questions (FAQ)

**Options:**

**HAL-QP-2X185LED-CPR-100-Cord Cap**

**Example:** HAL-QP-2X185LED-CPR-100-1523

Cord Cap	
5-15 125V	-1523
5-20 125V	-2023-125V
6-20 250V	-2023-250V

Links (Click on the below items to view):

- [HigResPic1](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)