

www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364

## Dolly Quadpod Portable Mast - 6' to 19' - Manual Crank Hand Winch - 100 lbs Payload - Aluminum

LM-DQP-19-6-4S-ALU

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



LM-DQP-19-6-4S-ALU Dolly Quadpod Light Mast

Height: 6` to 19` Weight: -Capacity: 100 lbs Materials: Aluminum

Operation: (1) Manual Hand Crank Winch Outriggers: (4) 37.75" - Retractable Cable: 3/16" Aircraft Cable

Mounting: Dolly Cart w/ (2) Rubber Tires

Shipping: Common Freight Shipping Dimensions: -Shipping Weight: +-375 lbs

Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

**Quick Summary** 

19` Portable Mast Aluminum Construction Removable Mast Head

**Special Orders- Requirements** 

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Intl: 1-214-616-6180 Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

## Made in the USA

The Larson Electronics LM-DQP-19-6-4S-ALU Dolly Quadpod Portable Mast provides a safe and effective way for operators to quickly deploy lights, security cameras and other equipment to elevations up to 19 feet. This temporary light tower comes with a removable mast head and is deployable using a manual hand crank winch. Constructed of lightweight aluminum, the unit is mounted on a dolly cart for seamless transportation.

## \*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS\*

The LM-DQP-19-6-4S-ALU is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in outdoor locations with minimal effort. This dolly quadpod is capable of reaching heights up to 19 feet for effective coverage and collapsed to 6 feet for storage. The tower is constructed of lightweight aluminum with a mast section that is 33 $^{\circ}$  in length and 2" x 2" x 1/8". The portable mast is elevated using an included manual hand crank winch with a 3/16" galvanized steel cable. When fully deployed, the dolly quadpod extends to 19 feet, with a base measurement of 93.5" x 75.5".

The LM-DQP-19-6-4S-ALU is constructed of aluminum. These portable masts are typically deployed during sporting events, concerts, large gatherings, outdoor conferences and emergency camp sites. For extra stability, four retractable

Larson Electronics LLC 9419 E US HWY 175, Kemp, TX 75143 Phone: 800.369.6671



www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364

outriggers measuring 37.75" each can be extended in a diagonal `X` configuration. A 33" wide,  $2'' \times 2'' \times 1/8''$  mounting plate is attached to the upper section of the mast which provides a strong and stable platform for light fixtures and equipment. The mast head component is removable for seamless storage and transportation. For storage, the unit can be collapsed down to 72.25"  $\times$  33"  $\times$  17.375".

This portable dolly quadpod can easily support and lift 100 lbs fixtures. The entire tower assembly is shipped via common freight carrier and when shipped weighs approximately 375 lbs. Larson Electronics can custom tailor these units to the customer's requirements with longer sections and larger mounting plates. For example, the LM-25 is a light tower model that reaches a length of 25 feet, with a 15 foot lower section, 10 foot upper section and a 4 foot wide upper mounting bracket. We also offer a choice of either the manual 1,000 lbs hand winches included standard or optional electric winches.

**Suggested Applications:** Temporary lighting, sports lighting, concerts, field lighting, outdoor conferences, stadium lighting, outdoor illumination, portable deployment, construction sites, and security camera deployment. We can equip this mast with 1000W or 1500W Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the <a href="LED10WSA-160"><u>LED10WSA-160</u></a>, <a href="LED1B-160X2E"><u>LEDLB-160X2E</u></a> or <a href="LEDLB-80x2E"><u>LEDLB-160X2E</u></a> or <a href="LEDLB-80x2E">LEDLB-160X2E</a> or <a href="LEDLB-80x2E">LEDLB-80x2E</a>.



www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364

## **Frequently Asked Questions (FAQ)**













www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- Video1
- Video2
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map