

12 Foot Telescoping Light Mast - 7-12' Hydraulic Two Stage Light Tower - 360° Rotating Boom LM-HA-12-7-2S-FM

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



LM-HA-12-7-2S-FM Two Stage Hydraulic Telescoping Light Tower

Length: 7 feet - 12 Feet

Weight: +-600 lbs

Capacity: 800 lbs

Materials: Steel

Finish: Powder Coated - Gloss Blue

Operation: Hydraulic

Mounting: 1/4" thick, 13"x15" Six Bolt Hole Bracket

Shipping: Common Freight

Shipping Dimensions: 10`-L x 4`-W x 5`-H

Shipping Weight: +-1200 lbs

Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

Quick Summary

7 to 12 Foot Light Mast

Steel Construction & Powder Coated Finish

Hydraulic Operation

Removable Mast Head

125 MPH Wind Resistance

Special Orders - Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The LM-HA-12-7-2S-FM from Larson Electronics is a 2-Stage Hydraulic Fixed Mount Light Mast that provides a safe and effective way for operators to quickly deploy lights, security cameras and other equipment to elevations up to twelve feet. This light tower folds over for easy transportation, features a rotating boom that allows for 360° of rotation, and a removable mast head for storing mounted equipment when not in use. The LM-HA-12-7-2S-FM can support up to 800 lbs of equipment at the full 12` height.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS, LIGHT TOWERS, OR QUADPODS

This telescoping two stage hydraulic steel light mast from Larson Electronics is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in locations where this equipment must be elevated to heights up to 12 feet for effective coverage. This light boom can be extended to 12 feet for maximum area coverage and collapsed to 7 feet for applications where a smaller footprint is required. The tower is constructed with a base stage of 4" x 4" x 1/8" square steel tubing measuring 6.52 feet in length and a second stage of 3" x 3" x 1/8" square steel tubing measuring 6.77 feet in length. The mast is elevated using hydraulics. The base stage and second stage are raised via a hydraulic ram. No manual winch is required at any point of the elevation process which makes operation convenient and easy.



[Click Photo to Enlarge](#)

[Click Photo to Enlarge](#)

The LM series of towers are powder coated with glossy blue finish for corrosion resistances and aesthetics. These light masts are typically mounted to trailers or other stable surfaces via a 15 inch by 13 inch, 1/4 inch thick mounting base-plate which has been drilled to accept six 3/4 inch anchor bolts. A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for mounted light fixtures or equipment. The LM family of telescoping towers feature a proprietary mast guidance system, which provide increased stability during high winds. When lowered to 7 feet, the mast can withstand winds up to 125 mph.

This light tower weighs approximately 600 lbs, can easily support and lift 800 lbs of light fixtures and other equipment. The entire tower assembly is shipped via common freight carrier and when shipped measures approximately 10 feet long, 4 feet wide, 5 feet tall and weighs approximately 1200 lbs. Larson Electronics can custom tailor these units to the customer`s requirements with longer sections and larger mounting plates. For example, the LM-30-3S is another model that reaches to a length of 30 feet, with a 14 foot lower section, 12 foot middle section, and a 8 foot upper section and a 4 foot wide upper mounting bracket.

Suggested Applications: Temporary lighting, construction sites, and security camera deployment. We can equip this mast with 1000W or 1500W Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the [LED10WSA-160](#), [LEDLB-200X2E](#), [LEDLB-160X2E](#) or [LEDLB-80x2E](#). At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)







Options:

LM-HA-12-7-2S-FM-Finish

Example: LM-HA-12-7-2S-FM-GLVD

Finish	
GALVANIZED	-GLVD
POWDER COAT	-PWDC

Links (Click on the below items to view):

- [Dimensional Drawing 2D](#)
- [STEP File \(3D CAD Model\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)