

Linear[®]**RADIO**

310 MHz
Stanley compatible
radio controls.



- For use with all dip-switch based Stanley garage door operators and gate control operators.
- Radios for all your garage door and gate operator applications.
- Single and multi-channel models; wide range of transmitter styles.

Miniature Transmitters



Mini Transmitters:

Model 308302 Two-Channel, Two-Button Transmitter

Micro Transmitter:

Model 108210 One-Channel, One-Button Transmitter

- Test/operate LED
- Molded-in hole to accept keychain or keyring
- Supplied velcro strip for visor or dashboard mounting
- Two-channel model (308302) operates two independent garage doors or an automatic gate and a garage door

Specifications

Power: long-life 12 V battery

Frequency: 310 MHz

Codes: 1,024 (set by dip switches)

Dimensions: mini (2.5 x 1.5 x .625 inches); micro (2 x 1.5 x .625 inches)

Handheld Transmitters



Model 105015 One-Channel, One-Button Transmitter

Model 109410 Two-Channel, Two-Button Transmitter

Model 109710 Four-Channel, Four-Button Transmitter

- Test/operate LED
- Easy access to battery and dip switch
- Two-channel model (109410) operates two independent garage doors or an automatic gate and a garage door; four-channel model (109710) provides control of up to four separate operations

Specifications

Power: long-life 9 V battery

Frequency: 310 MHz

Codes: 1,024 on one and two-channel models; four-channel features two sets of dip switches, offering 512 codes each

Dimensions: 3.75 x 2.5 x .875 inches

Gate Edge Transmitters



Model 105104 Wireless Safety Edge Transmitter

- For use with safety edges on gates and large commercial doors
- Can be used where hard wires are impractical
- Easy to install and mount
- More economical than coil/cord sets

Specifications

Power: 9 V battery

Frequency: 310 MHz

Codes: 1,024 (set by dip switches)

Dimensions: 4 x 4.28 x 2.22 inches

Wall-Mounted Lighted Keypads



Model 298601 Wireless Keypad

- Tamper-resistant and weatherproof
- Easy mounting with two screws
- 12-button, alphanumeric keypad
- LED mode indicator

Specifications

Power: 9 V battery

Frequency: 310 MHz

Codes: 4-digit PIN code access

Dimensions: 2.75 x 6.25 x 1 inches

Receivers

Model 309013 General Purpose Digital Receiver

- Exclusive two-way lugs that fit right under terminal screws or accept push-on terminals in remote sites
- 11-inch wire antenna supplied
- Three tabs for universal operator mounting

Specifications

Power: for connection to any three-terminal 24 V operator (for higher voltages, consult factory); no need for transformer or adapter

Frequency: 310 MHz

Codes: 1,024 (set by dip switches)

Dimensions: 3 x 5.5 x 1.5 inches

Model 109931 Gate Receiver

- For use inside metal enclosures and in other applications requiring stronger signal reception
- Antenna with coaxial connector supplied
- 1 amp output @ 30 Vac maximum on relay contacts

Specifications

Power: 24 V input

Frequency: 310 MHz

Codes: 1,024 (set by dip switches)

Dimensions: 5.25 x 3.625 x 1.5 inches

Model 203102 Light-Duty Commercial Gate Receiver

- For any application requiring two channels in one location—512 codes each channel
- Housed in light, stamped steel cabinet
- Ideal for sites with dual-channel requirement and a protected environment
- Two-channel relay output, N/O, N/C, Common-rated 1 amp @ 30 Vac max

Specifications

Power: 24 Vac

Frequency: 310 MHz

Codes: 1,024 total (set by dip switches); 512 codes each of two channels

Dimensions: 6 x 8 x 2 inches

Linear®

2055 Corte Del Nogal, Carlsbad, CA 92009

(760) 438-7000 (800) 421-1587 Fax (800) 468-1340

www.linearcorp.com