

## **Exit Button** LTKB04

**Accessary of Magnetic Lock** 

## **Features:**

- Dimension (L $\times$ W $\times$ H): 90 $\times$ 35 $\times$ 37.7mm(3.54 $\times$ 1.38 $\times$ 1.48");
- Input Voltage: DC12V;
- Working Current: 20mA(standby), 50mA(working current);
- Current Rating: 1A@30VDC,0.5A@125VAC;
- Output Contact: NO/NC/COM Contact;
- Panel: aluminum panel;
- Aging Test: already passed 1 million times aging test;
- Suitable Doors: all kinds of narrow doorframes;
- Working Temperature:  $-20^{\circ}$  C to  $+50^{\circ}$  C ( $-4^{\circ}$  F to  $122^{\circ}$  F);
- Working Humidity: 0 to 95% (relative humidity);
- Maximum Inductive Distance: 40 to 100mm(1.57 to 3.94") (adjustable);
- LED Indicator Status: white/green/red LED, indicates power-off/active/Standby;
- Product Weight: 0.12kg (0.26lb).

## **Dimensions and Installation:**

## Dimension $\bigcirc$ EXIT Installation Detection range: 4-10cm(Adjustable) Time delay:0.5S~25S VR1 illustration" VR2 illustration" ⊗ Max.detection distance ⊕ Min.detection distance ⊕ Max.time delay

©2018 LT Security, Inc. All Rights Reserved. White papers, data sheets, quick start guides, and/or user manuals are for reference only and may or may not be entirely up to date or accurate based upon the version or models. Product names mentioned herein may be the unregistered and/or registered trademarks of their respective owners.







