



ExtIO Opens New Horizons For Cameras

With its new ExtIO module, MOBOTIX leads the way to completely new technology. The ExtIO can be connected to a camera either directly via USB or through a network and extends the MOBOTIX camera to a high-performance audio unit with microphone and speaker, infrared motion detector, temperature sensor and additional switch in-/outputs. Door and gate intercom systems are easy to implement using the two illuminated buttons.

Technical Specifications ExtIO

Interfaces	USB, Ethernet 10/100 Mbps (from Q3/2008)	Status display	2 Status LEDs
Audio	Microphone and speaker, integrated amplifier and equalizer	Certificates	EMV (DIN 61000), FCC Part 15 for Class B Devices,
Input contacts	2 Signal inputs (galvanically separated) Safety extra-low voltage, SELV (AC/DC) Switching voltage of ExtIO provided (also external)	Operating conditions	IP65 (DIN EN 60529)
Output contacts	2 Signal outputs (potential-free) Safety extra-low voltage, SELV (AC/DC), up to 100 mA	Operating temperature	-30° to +60 °C (-22°F to +140°F) (DIN EN 50125)
Sensors	Passive IR motion detector (PIR) Temperature sensor for room temperature Dawn sensor IR remote sensor 2 illuminated buttons	Power supply	USB, Power over Ethernet (PoE)
		Power input	typ. 1 W
		Dimensions	Ø x H: 16 x 4,5 cm, compatible with D22 accessories
		Weight	ca. 430 g
		Standard delivery	Housing (high-resistance composites - PBT-30GF), white, speaker cable, mounting parts, patch cable, manual

Technical information subject to change without notice!

ExtIO

Available Accessories for ExtIO

ExtIO Extension Module MX-ExtIO	In-Ceiling Set MX-D22M-OPT-IC	On-Wall Set MX-D22M-OPT-AP	Vandalism Set MX-D22M-Vandal-Kit-ESPO	Outdoor Wall Mount MX-D22M-OPT-WH	Pole Mount MX-D22M-OPT-MH
 <ul style="list-style-type: none"> • Microphone/speaker • IR motion detector (PIR), temperature sensor • Signal input/Signal output 	 <ul style="list-style-type: none"> • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Ø 150 mm installation dimension 	 <ul style="list-style-type: none"> • Consists of on-wall mount and mounting parts • Reliably protects the cabling • 165 mm x 37 mm 	 <ul style="list-style-type: none"> • Stainless steel cover (polished or matt, in white, silvergray or black) 	 <ul style="list-style-type: none"> • Weatherproof (IP65) for ExtIO • Covers RJ45 wall outlets • Space for expansion modules (WLAN) 	 <ul style="list-style-type: none"> • 3 mm stainless steel, white • 2 stainless steel straps for pole diameter 60-180 mm, incl. mounting parts

* 2008/04 • Manufacturer's suggested retail prices • Prices ex works Kaiserslautern Germany • Excl. VAT and country specific customs taxes • Subject to change without notice

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG • D-67657 Kaiserslautern • Tel: +49-631-3033-103 • Fax: +49-631-3033-190 • sales@mobotix.com