



## EasyNet™ Pro Series ED-P400/P800/P1600



### Product Description

- Available in 4, 8, & 16-ch
- Embedded Linux operating system
- Pentaplex function - simultaneous live / record / playback / network / file copy
- Recording compression method: H.264
- Real-time recording per channel
- Multiple monitor outputs & Looping video outputs
- DVR control options: Front panel, IR remote, PC mouse, Keyboard (CK-1000)
- File copy method: Built-in DVD burner or USB flashdrive
- Multi-channel audio support
- Watermark
- Time synchronization between multiple DVRs
- Firmware upgrade via USB or network
- VMS Pro - Windows PC & Mac compatible
- Free mobile app
- Free DDNS service

### Advanced Features



#### Multi-Layer Streaming™

When monitoring live over a network, EasyNet™ DVRs transmit 3 video streams simultaneously for optimal network performance. Independent of the actual frame rate and resolution being recorded by the DVR, these secondary and tertiary streams represent an ideal solution for low bandwidth environments such as DSL and 3G networks.

- Primary Stream (H.264): User defined recording frame rate & resolution per channel
- Secondary Stream (H.264): 2pps @ CIF per channel(Fixed)
- Third Stream (M-JPEG): 2pps @ CIF per channel(Fixed)



#### Copy Files & Playback from DVR

For your convenience, recorded files can be copied and archived to a USB flashdrive or CD/DVD in multiple formats.

- NVF (NUVICO File System) - Our new proprietary & tamper proof file system, also allows playback from any EasyNet™ DVR
- EXE (NVF w/ mini player)
- MP4 - A standard format where copied files can be reviewed from Windows PC or Mac, without using any 3rd party software



#### Widescreen Support (16:9)

New EasyNet™ DVRs utilize the latest HD Mux & Decoder chip sets available. Designed to accommodate modern-day HD widescreen monitors, EasyNet™ DVRs deliver industry-leading display resolution.



#### EasyNet Touch™ - Free Mobile App

NUVICO's new app allows the user to access video streams directly from EasyNet™ DVRs to their handheld devices over Wi-Fi or 3G/4G networks. In addition to remote video monitoring, our powerful app incorporates many advanced features required in everyday security environments:

- Display up to 16 cameras in both live view & playback
- Favorite camera group setup from multiple DVRs
- Instant playback
- Time Search
- DVR status icons - Recording On/Off, Alarm, Video Loss & HDD fail
- PTZ controls



#### Multi-Layer Recording™

A derivative of NUVICO's exclusive Multi-Layer Streaming™ technology, Multi-Layer Recording allows a user to quickly review recorded files over a network, which is as important as live video monitoring. Multi-Layer Recording™ gives you the option to record 3 independent video streams in tandem. This powerful function makes faster remote search and playback possible. This feature is especially useful when performing multi-channel playback over a low bandwidth network.

- Primary Stream (H.264): User defined recording frame rate & resolution per channel
- Secondary Stream (H.264): 6pps @ CIF per channel (Fixed)
- Third Stream (M-JPEG): 2pps @ CIF per channel (Fixed)



#### RTSP: Real Time Streaming Protocol

In addition to Multi-Layer Streaming™, we have integrated an RTSP server into the new EasyNet™ DVRs. RTSP enables an unlimited number of users to access live video streams using a common media player such as QuickTime™, which is available for both a Windows PC and Mac. Simple but effective, this is an ideal approach to applications requiring a large number of simultaneous users, such as a university campus, construction site, day-care center, pet shop, marina, and the like.






#### EasyNet™ VMS Pro

Our new multi-site management software exclusively developed for new EasyNet™ DVRs, as well as our upcoming EasyNet™ IP cameras and NVRs. Built on a universal software platform, EasyNet™ VMS Pro works flawlessly on both a Windows PC and Mac.

- Register and manage up to 1,000 DVR sites
- View up to 128 cameras from multiple sites simultaneously
- Memory reserve for event and system status log - 10,000 events
- Intelligent PC resource & network bandwidth management
- E-map
- 2 - way Audio
- Multiple monitor support
- Windows PC & Mac compatible



## Technical Specifications

EasyNet™ Pro Series	ED-P400 	ED-P800 	ED-P1600 
<b>Video Format</b>	NTSC / PAL Auto Detect	NTSC / PAL Auto Detect	NTSC / PAL Auto Detect
<b>Video Compression</b>	H.264	H.264	H.264
<b>Operating System</b>	Embedded Linux	Embedded Linux	Embedded Linux
<b>Pentaplex Function</b>	Simultaneous Live / Record / Network / Playback / File Copy		
<b>Video Input / Loop Output</b>	4 / 4	8 / 8	16 / 16
<b>Maximum Recording Rate &amp; Resolution</b>	120pps @ CIF	240pps @ CIF	480pps @ CIF
	120pps @ 2CIF	240pps @ 2CIF	240pps @ 2CIF
	120pps @ 4CIF	120pps @ 4CIF	120pps @ 4CIF
<b>Monitor Output - Main 1</b>	VGA (1440 x 960), BNC	DVI/HDMI (1920 x 1080), VGA, & BNC	DVI/HDMI (1920 x 1080), VGA, & BNC
<b>- Spot 1 (BNC: Composite)</b>	(Full / Sequence)	(Full / Sequence)	(Full / Sequence)
<b>- Spot 2 (BNC: Composite)</b>	N/A	(Full / Sequence)	(Full / Sequence)
<b>- Spot 3 (BNC: Composite)</b>	N/A	N/A	N/A
<b>- Spot 4 (BNC: Composite)</b>	N/A	N/A	N/A
<b>Network Transmission Method</b>	Selectable	Selectable	Selectable
<b>- Primary Stream</b>	H.264 @ User-defined resolution	H.264 @ User-defined resolution	H.264 @ User-defined resolution
<b>- Secondard Stream</b>	H.264 @ CIF	H.264 @ CIF	H.264 @ CIF
<b>- Third Stream</b>	M-JPEG @ CIF	M-JPEG @ CIF	M-JPEG @ CIF
<b>Internal Storage</b>	1 Internal HDD bay (Up to 2TB)	3 Internal HDD bay (Up to 6TB)	3 Internal HDD bay (Up to 6TB)
<b>Alarm In/Out</b>	4 Inputs / 1 Output	8 Inputs / 2 Output	16 Inputs / 4 Output
<b>Audio In/Out</b>	4 Inputs / 1 Output	8 Inputs / 1 Output (Optional)	16 Inputs / 1 Output
<b>Audio Over Network</b>	2-way	2-way	2-way
<b>PTZ Dome &amp; Controller Interface</b>	RS-485	RS-485	RS-485
<b>Network Port</b>	Gigabit Ethernet	Gigabit Ethernet	Gigabit Ethernet
<b>Built-in Copy Device</b>	CD / DVD Burner (Max 4GB Clips)	CD / DVD Burner (Max 4GB Clips)	CD / DVD Burner (Max 4GB Clips)
<b>External Copy Device</b>	USB Flashdrive (Max 2GB Clips)	USB Flashdrive (Max 2GB Clips)	USB Flashdrive (Max 2GB Clips)
<b>USB Ports</b>	2 Front, 1 Rear	2 Front, 1 Rear	2 Front, 1 Rear
<b>Recording Modes</b>	Continuous, Schedule, Alarm, Motion, and Panic Recording		
<b>Recording Adjustments</b>	Resolution, frame rate, and picture quality per channel		
<b>Pre-event &amp; Post-event Recording</b>	Pre-recording: 5 sec, per channel / Post-recording: 240 sec, per channel		
<b>Search Mode</b>	Time / Calendar / Event Search	Time / Calendar / Event Search	Time / Calendar / Event Search
<b>Alarm Notification</b>	Pop up, buzzer, e-mail, and relay	Pop up, buzzer, e-mail, and relay	Pop up, buzzer, e-mail, and relay
<b>Watermark / Time Sync.</b>	Yes / Yes	Yes / Yes	Yes / Yes
<b>Power Failure Recovery</b>	Auto reboot while maintaining system settings		
<b>Rack Mount Kit</b>	Yes (Optional)	Yes (Optional)	Yes (Optional)
<b>Operating Temperature</b>	41°F ~ 104°F (0°C ~ +40°C)	41°F ~ 104°F (0°C ~ +40°C)	41°F ~ 104°F (0°C ~ +40°C)
<b>Dimensions (W-D-H) mm</b>	14.53" x 15.35" x 3.46" (369mm x 390mm x 88mm)		
<b>Power Input</b>	AC 100 ~ 240V, 50/60 Hz, 85W Max, Typical 60W		

## Available Models

HDD Capacity	Model Number	HDD Capacity	Model Number	HDD Capacity	Model Number
1TB	ED-P410	1TB	ED-P810	1TB	ED-P1610
2TB	ED-P420	2TB	ED-P820	2TB	ED-P1620
		3TB	ED-P830	3TB	ED-P1630
		4TB	ED-P840	4TB	ED-P1640
		6TB	ED-P860	6TB	ED-P1660

### \*Minimum System Requirements (Single site mode)

<b>OS:</b>	Windows 7 or Mac OS X 10.6
<b>CPU:</b>	Core 2 Duo
<b>Memory:</b>	2GB
<b>Video Card:</b>	1GB
<b>Network:</b>	100Mbps

### \*Preferred System Requirements (Multi-site mode)

<b>OS:</b>	Windows 7 or Mac OS X 10.7
<b>CPU:</b>	Core i7
<b>Memory:</b>	16GB
<b>Video Card:</b>	8GB
<b>Network:</b>	1Gbps

# ED-P400/P800/P1600



**NUVICO Corporate Headquarters**  
53 Smith Street Englewood, NJ 07631  
Tel: 201-541-1605 Toll Free: 866-523-1700 Fax: 201-541-1620  
sales@nuvico.com | www.nuvico.com

**NUVICO International Corporation**  
R#1001, KOFOMO Tower, 16-3 Sunae-Dong, Bundang-Gu,  
Seongnam-Si Gyeonggi-Do, 463-825, Korea  
Tel: 82-31-712-8814 Fax: 82-70-7500-9164 | export@nuvico.com