

NUVICO®

HD-Pack

4ch Full HD NVR with Built-in POE
& 4 Outdoor Bullet Cameras

NP-P402



Product Description

- Watch live, network video and record real-time in full 1080p HD quality
- Built-in 4 POE ports turns a small IP installation into an easy plug & play
- No more expensive POE switches
- Free mobile apps for Apple and Android mobile devices
- Separate POE power adapter for stable power
- Built-in HDMI for a local HD display
- 4 Outdoor bullet cameras with LEDs

Technical Specifications

NVR X 1		
Compression	Video	H. 264 HP supported
	Audio	ADPCM, PCM supported
HDD Interface		1ea x SATA I / II / III (Max 2TB)
Operating System		Embedded Linux
Video output		HDMI (1280X720p/1920x1080p/1280x1024/1024x768)
Live & Playback	Decoding	Live display @ 1080p
	Display mode	1/4 auto sequence
	Search mode	Date/Time, Record Table, Calendar, Event, Bookmark, Play from Search, System log
Record	Main Stream	Max 120fps @ 1080p
	2nd Stream	Real-time up to D1
	mode	Continuous, Event, Pre-alarm, Post-alarm
Network	Interface	1 x 10/100/1000Mbps WAN port 1 x 10/100Mbps LAN port
	Protocol	TCP/IP, DHCP, NTP, HTTP, DDNS, RTP, RTSP, FTP, SMTP, OnViF, uPnP, IPv6
	Monitoring	Network Bandwidth / Camera Status / Access Log / Accessed Info / Alarm / Motion
Interface	USB	2 X USB 2.0
	Serial	N/A
PoE		4 ports (802.3 AF supported)
Mobile		iPhone, iPad, Android
Web Browsing		Yes
Audio In / Out		1 x Audio in, 1 x Audio out
Alarm		1/1
Power	Main : 12V / 3A	
	PoE : 48V / 1.4V	
ETC		Mouse, LED (Power, HDD, Network)
Operating Temperature		0° ~ 40°
Operating Humidity		0% ~ 90%
Accessories		Mouse
Approvals		FCC, CE Approval

CAMERA X 4	
Image Sensor	1/2.8" CMOS
Lens	3.6mm Fixed
Scanning Mode	Progressive Scan
Min. Illumination	Color: 2.5 Lux, B/W: 0. Lux @ F1.2, 50IRE
AE/AWB	Yes
DNR	2DNR / 3DNR
D&N	True D&N (IR-cut filter)
WDR	Yes
LEDs	24 LEDs (Up to 80ft)
Progressive Encoding	Yes
Compression	H.264(BP/MP/HP), MJPEG
Resolution Supported	1080p, 1280x1024, 720p
Frame Rate	30fps @ all resolutions
Multiple Streaming	Dual
Audio In/Out	No
Alarm In/Out	No
RS485	No
Ethernet	10/100Mbps
Local Storage	No
Motion Detection	Yes
Network Protocols	IPv4/IPv6, Manual TCP/IP, UDP, HTTP, RTP, RTSP, NTP, DHCP, SMTP, DDNS, HTTPS, RTCP, FTP, Bonjour
Weatherproof	IP66
PoE	Yes
Power	PoE, DC12V
Power Consumption	6.0W
Operating Temperature	0° ~ 50° C
Humidity	0% ~ 90% RH
External Dimension	70(W) X 70(H) X 155(D)mm
IR LED Illuminated Angle	80°



NUVICO Corporate Headquarters
53 Smith Street Englewood, NJ 07631
Tel: 201-541-1605 Toll Free: 866-523-1700 Fax: 201-541-1620
sales@nuvico.com | www.nuvico.com

NUVICO International Corporation
R#1001, KOFOMO Tower, 16-3 Sunae-Dong, Bundang-Gu,
Seongnam-Si Gyeonggi-Do, 463-825, Korea
Tel: 82-31-712-8814 Fax: 82-70-7500-9164 | export@nuvico.com