



- 150-250 tenants and 150-250 access codes
- Local programming via keypad with audio prompts
- 1x16 Electronic Liquid Crystal Display (LCD)
- Backlit Keypad Button
- Non-Volatile memory
- Single Relay
- Support pause dialing from the PBX
- Indoor or outdoor, surface and full-flush mount.
- Brushed Stainless Steel Faceplate

Warranty: 24 month

Purchase UPS2L, will include lightning on 24 months warranty

SPECIFICATIONS

POWER INPUT: 12VAC/40VA (supplied) or 12-VDC/40VA with battery backup charging circuit.

CURRENT CONSUMPTION: 500mA idle, 700mA operating.

OPERATING ENVIRONMENT: 32°F to 140°F. *Heater is required if the temperature is below 32°F.*

NIGHT LIGHT: Super Bright Light Emitting Diode (LED).

CONSTRUCTION: 16 Gauge Cold Rolled Steel back box with enamel finished and Brushed Stainless Steel Faceplate

MOUNTING: Surface and full-flush.

DIMENSIONS:

Surface 10-13/16 "(H) x 8-5/8 "(W) x 3-3/4 "(D).

Full-flush 10-13/16 "(H) x 8-3/8 "(W) x 2-7/16"(D)

MOUNTING RING FULL-FLUSH (FFM7 is included on 7150FFP and 7250FFP):

Inside 11-1/8" (H) x 8-11/16"(W) x 2-5/8"(D)

Outside 14-5/16" (H) x 12-1/8" (W)

SHIPPING WEIGHT: 10-12 lbs approximate.

ORDERING PART

Surface Mount

7150P

150 tenants 150 access codes

7250P

250 tenants 250 access codes

Full-flush Mount

7150FFP

150 tenants 150 access codes

7250FFP

250 tenants 250 access codes

ACCESSORIES

Video Package

UVPC Color Camera Package

UVPB Video Balun for Twisted Pair video transmission

Pedestal Mounting Post, Adapter Plate and Mounting Ring

UPM1S Standard Single Arm (42"H, 5"x5" base)

UPM4S Standard Single Arm (47"H, 5"x5" base)

UPM1L Large Single Arm (47"H, 8"x8" base)

UPM6L Large Single Arm (64"H, 8"x8" base)

UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)

UPM5 Double Horizontal Arm (47"H, 8"x8" base)

UPMDB64 Single Arm Direct Buriel (64"H)

UAP78 Adapter Plate AeGIS 8000P Series

UPM12E 12" Expansion Arm use for all UPM

Miscellaneous Accessories

USP1 AC and Telephone Surge Protector.

USP2L Surge and Lightning Protection, *include Lightning on 24 months warranty*

AHP5 Heater Pad with Thermostat.

UBAT1 12VDC 4.5 Amp Hour backup battery.

UXIT Multipurpose push button switch

Specifications subject to change without prior notice