



Communication Systems

6670 185th Ave NE * Redmond, WA 98052 * (425) 455-0510 * (800) 692-0200

Wire Specification Sheet

Aiphone Wire # 851602

Description: 16 AWG 2 conductors solid bare copper wire with foamed PE insulation, unshielded and an overall PVC jacket for low-voltage electronic cable applications.

1. Conductor

- 1.1. AWG Size & Stranding: 16 AWG Solid
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 2 Conductors

2. Insulation

- 2.1. Material: Foamed PE
- 2.2. Wall Thickness: 0.015"
- 2.3. Color Code: Black, Red

3. Cable Assembly

- 3.1. Nominal Lay Length: 2.50" LHL (4.80 Tw/Ft)
- 3.2. Shield: N/A
- 3.3. Drain Wire: N/A

4. Jacket

- 4.1. Material: Polyvinylchloride
- 4.2. Wall Thickness: 0.015"
- 4.3. Diameter: 0.192" ± .015"
- 4.4. Color: Dark Gray
- 4.5. Ripcord: Yes
- 4.6. Weight: 24 Lbs/Mft

5. Markings*

- 5.1. Type: Cable permanently identified via surface inkjet print
- 5.2. Legend: AIPHONE P/N 851602 E171202 16AWG 2C 75°C (UL)
CL3 OR FPL OR C(UL)US CM "ROHS II" MADE IN USA
- 5.3. Footage Markers: Yes

6. Nominal Electrical Characteristics

- 6.1. Impedance: 100 Ω
- 6.2. Capacitance: 14 pF/ft.
- 6.3. Conductor DCR: 4.02 Ω/Mft. @ 20°C Maximum

7. Standards

- 7.1. Refer to NEC (NFPA 70) article 725, 760 and article 800 for installation guidelines
- 7.2. UL listed as type CL3 per UL standard 13, type CM c(UL)us 75° C per UL standard 444, and as type FPL per UL standard 1424
- 7.3. All materials used in the manufacturing of this cable are RoHS II and REACH compliant
- 7.4. Maximum Operating Voltage: 300V RMS
- 7.5. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION

ALL MEASUREMENTS ARE NOMINAL

Rev A 042017