



DESCRIPTION

The GT-1C7W is an app-compatible audio/video tenant station for the GT Series Multi-Tenant system. The 7" touchscreen allows for various functions. These include answering an incoming call, door release, and triggering an optional output. Additional controls include screen brightness, Pan, Tilt, Zoom (PTZ), and guard call.

When a visitor calls, the tenant station will display video on the screen and call up to eight mobile apps. The call is answered by touching the talk button. The GT-1C7W has the capability of calling the concierge/security guard station(s), turning on an external light while speaking with a visitor at the entrance, and receiving an emergency tone from a pull cord or panic call button.

The GT-1C7W has a slim, streamlined, surface mount design. Only one GT-1C7W video station can be used per tenant.

Communication is hands-free at the entrance station when a tenant answers the call. While speaking with the visitor, the GT-1C7W can communicate with either hands-free (VOX) or push-to-talk (PTT) functionality.


FEATURES

- 7" touchscreen
- Aiphone Type GT App compatible (Up to 8 apps)
- Hands-free audio communication
- Door release
- Concierge/security guard call
- PTZ and brightness control
- Call tone volume control
- Communication volume control

GT-1C7W

GT Series App-Compatible Video Tenant Station with 7" Touchscreen

FEATURE CALL-OUT



FEATURE CALL-OUT DEFINITIONS

- [1] 7" touchscreen
- [2] Reset button
- [3] Microphone
- [4] microSDHC™
- [5] Speaker

SPECIFICATIONS

- Power Source:** 24V DC
(Use PS-2420UL or GT-4ZP)
- Current:** 300mA (max)
- Communication:** Hands-free or Push-to-talk
- Screen:** 7" TFT LCD
- Mounting:** Surface wall mount
- Temperature:** 32~104°F (0~40°C)
- Dimensions:** 6-1/8" H x 8-1/4" W x 1-1/16" D
- Weight:** Approx. 1.37 lbs (620g)
- microSDHC™:** 4-32 GB (FAT32) Class 10
- WLAN interface:** IEEE802.11b/g/n
- Upload/Download:** Minimum 3 Mbps