

#### DESCRIPTION:

The IS-SS-RA-R is a stainless steel flush mount audio door station with an emergency call button. The unit is equipped with ADA compliant lettering and Braille signage. A call status indicator is included to meet ADA assistance requirements.

The emergency button will trigger two selectable relay outputs for activation of external systems or devices.

The IS-SS-RA-R unit will connect with CAT-5e or CAT-6 wire to any control unit in the hardwired IS system (IS-CCU, IS-SCU, or IS-RCU), giving you a greater capacity of rescue assistance subs. A directory strip for location identification is also provided. The unit is made of stainless steel and includes tamper resistant screws.

#### FEATURES:

- Audio communication between master station and calling area
- Emergency call button
- Two selectable relay outputs
- ADA compliant lettering and Braille signage
- LED call status indicator
- Stainless Steel faceplate with tamper resistant screws



# IS-SS-RA-R

Stainless Steel Flush Mount Audio Door Station with Emergency Call Button

## FEATURE CALL-OUT DEFINITIONS:

- [1] Microphone
- [2] Speaker
- [3] Directory card
- [4] Call status indicator
- [5] Call button
- [6] Emergency signage with Braille

## SPECIFICATIONS:

- Power Source: 48VDC (supplied from CEU)
- Communication: Open voice hands-free
- Wiring: CAT-5e or CAT-6
- Wiring distance: 980'
- Door release: 24V AC/DC, 500mA (N/O, COM, N/C)
- Operation Temp: 14° - 140°F (-10° - 60°C)
- Dimensions: 7" W x 11-3/4" H x 1-7/8" D

## FEATURE CALL-OUTS:

