

# SP-2570N

## Flush Mount Ceiling Speaker

**DESCRIPTION:**

The SP-2570N is a ceiling speaker used for paging and background music. It is equipped with a 25/70V transformer with five wattage taps up to 4W. The speaker is mounted to a round steel baffle, finished with a white powder-coated epoxy. An optional ceiling support bridge (SSB-2) is available for installations in drop tile ceilings.

Designed for indoor use only.

**SP-2570N****FEATURES:**

- 8" dual cone speaker, 8 ohms
- 25 or 70V transformer
- Five wattage taps from 1/4W to 4W
- Round white steel baffle
- Excellent sound reproduction for music and paging

**SSB-2**

Mounting bracket for drop tile ceiling

**TRANSFORMER WATTAGE TAPS:**

70.7V LINE		25V LINE	
Com:	Black	Com:	Black
5W:	Green	5W:	Brown
2.5W:	White	2.5W:	Red
1.25W:	Blue	1.25W:	Orange
.625W:	Gray	.625W:	Green
.312W:	Violet	.325W:	White

Secondary (Speaker direct): 8 Ohms

**SPEAKER SPECIFICATIONS:**

Size:	8"
Magnet Weight:	5 oz.
Magnet Material:	Ceramic
Voice Coil Impedance:	8Ω
DC Resistance, ohms:	7.4Ω
Voice Coil Diameter:	3/4"
Power Handling:	8W RMS
Frequency Response:	65 to 17K Hz.
Depth:	2-3/4"
Weight:	1.75 lbs.
Cone:	Dual

**BAFFLE SPECIFICATIONS:**

Type:	One-step contour
Baffle Diameter:	12-7/8"
Material:	22 gauge steel zincrometal
Finish:	White semi-gloss powdered epoxy
Depth Projection:	3/8" from surface
Weight:	1.5 lbs.

SP-2570N-SS 0807