

## AXIS P3915-R Mk II Network Camera

Onboard HDTV 1080p surveillance with audio and Zipstream

AXIS P3915-R Mk II Network Camera is specifically designed for video surveillance in vehicles and rolling stock. The compact, discreet, and rugged camera is IP66/IP67-rated, and can withstand tough conditions such as vibration, shock and temperature fluctuations. Optional accessories for outdoor installation and wider field of view available. The camera provides HDTV 1080p with WDR and Lightfinder to ensure high image quality in mixed and low-light conditions. Traffic Light mode enables the camera to distinguish traffic light colors in dark scenes. Audio-in and I/O capabilities optimize smart surveillance in the driver's compartment. AXIS P3915-R Mk II supports Zipstream, which significantly reduces bandwidth and storage requirements.

- > **Rugged design with EN 50155:2017 Class OT2/ST2 compliance**
- > **Compliance with strict standards in transportation industry**
- > **WDR - forensic capture and Lightfinder**
- > **Zipstream**
- > **Traffic Light mode**
- > **Audio-in and I/O ports**



# AXIS P3915-R Mk II Network Camera

<b>Models</b>	AXIS P3915-R Mk II: RJ45 AXIS P3915-R Mk II: M12	Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation	
<b>Camera</b>			
<b>Image sensor</b>	1/2.9" Progressive scan RGB CMOS	<b>Data streaming</b> Event data	
<b>Lens</b>	3.6 mm, F2.0 Horizontal field of view: 87° Vertical field of view: 47° M12 mount, fixed iris See <a href="#">Optional accessories</a> for exchangeable lenses	<b>Built-in installation aids</b> Pixel counter	
<b>Light sensitivity</b>	HDTV 1080p 25/30 fps with Lightfinder Color: 0.15 lux at 50 IRE F2.0 Color: 0.06 lux at 30 IRE F2.0	<b>General</b>	
<b>Shutter time</b>	1/32500 s to 2 s	<b>Casing</b> Aluminum and polycarbonate casing	
<b>Camera angle adjustment</b>	Pan: ±30°, tilt: 15-90°, rotation: ±175°	<b>Sustainability</b> PVC free	
<b>Video</b>			
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Mounting</b> Inside vehicles and rolling stock	
<b>Resolution</b>	1920x1080 to 160x90	<b>Memory</b> 512 MB RAM, 256 MB Flash	
<b>Wide dynamic range</b>	WDR - forensic capture	<b>Power</b> Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 3.3 W, max 3.9 W	
<b>Frame rate</b>	Up to 25/30 fps (50/60 Hz) in all resolutions	<b>Connectors</b> RJ45: male, 10BASE-T/100BASE-TX M12: female, rugged, D-coded with rotatable coupling nut All connectors support PoE 3.5 mm audio in connector, mono, I/O 4-pin, 1 input, 1 output + 12 V DC/15 mA	
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	<b>Storage</b> Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="#">www.axis.com</a>	
<b>Image settings</b>	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, text and image overlay, 20 individual privacy mask, mirroring of images, Traffic Light mode	<b>Operating conditions</b> Normal: -40 °C to 60 °C (-22 °F to 140 °F) Maximum (intermittent): 70 °C (158 °F) Arctic Temperature Control: start-up at -40 °C (-40 °F) Humidity: 10-100% RH	
<b>Pan/Tilt/Zoom</b>	Digital PTZ, preset positions Guard tour, control queue	<b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F)	
<b>Audio</b>			
<b>Audio streaming</b>	Audio in, simplex	<b>Approvals</b> EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.05 (E approval), EN 50498, EAC	
<b>Audio compression</b>	AAC- LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	<b>Safety</b> IEC/EN/UL 62368-1, EN 45545, UN ECE R118, parts of NFPA 130 <sup>c</sup>	
<b>Audio input</b>	External microphone input or line input	<b>Environment</b> IEC/EN 61373 Category 1 Class B, IEC/EN 60529 IP66/67, NEMA 250 Type 4X, IEC/EN 62262 IK08, IEC 60721-3-5 Class 5M3 (vibration and shock), EN 50155:2017 Class OT2/ST2 (EN 50155:2007 Class TX), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78	
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, network access control, digest authentication, user access log, centralized certificate management	<b>Dimensions</b> Height: 49 mm (1 15/16 in), ø 109 mm (4 3/16 in)	
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	<b>Weight</b> RJ45: 255 g (0.56 lb) M12: 264 g (0.58 lb)	
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="#">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="#">www.onvif.org</a>	<b>Included accessories</b> Installation guide, Windows decoder 1-user license, drill hole template, top cover tool, lens tool, Allen key Resistorex <sup>®</sup>	
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, active tampering alarm <sup>b</sup> , audio detection <b>Supported</b> AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="#">www.axis.com/acap</a>	<b>Optional accessories</b> Lenses 2.1 mm, F2.2: horizontal field of view 147° 2.8 mm, F2.0: horizontal field of view 115° 6 mm, F1.6: horizontal field of view 52° 8 mm, F1.6: horizontal field of view 40° <b>Other</b> AXIS T94D01S Mount Bracket, AXIS T94D02S Mount Bracket, Network coupler IP66, Network cable coupler indoor For more accessories, see <a href="#">www.axis.com</a>	
<b>Event triggers</b>	Analytics, time scheduled, edge storage events Audio level, external input	<b>Video management software</b> AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on <a href="#">www.axis.com/support/downloads</a>	
<b>Event actions</b>	Record video and audio: SD card and network share Upload images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload	<b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
		<b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="#">www.axis.com/warranty</a>	

- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](#)), and cryptographic software written by Eric Young ([eay@cryptsoft.com](#)).
- For detection of tampering attempts in static and non-crowded scenes.
- ASTM E162 and the non-flaming parts of ASTM E662