

## AXIS T94K02L Recessed Mount

Discreet installation in drop ceilings

AXIS T94K02L Recessed Mount is designed for indoor drop ceiling installations, and is suitable for AXIS P32-V/-LV series, AXIS P33/-V/-LV series, AXIS Q35-V/-LV series network cameras. The recessed mount is applicable for indoor environments and is suitable for installation in air-handling (plenum) spaces as the enclosure is made of metal alloy with both 1/2" (M20) and 3/4" (M25) conduit holes for protected cable routing.

- > Supports a wide range of indoor fixed dome cameras
- > Quick and easy indoor drop ceiling installations
- > Support for 1/2" (M20) and 3/4" (M25) conduits



## AXIS T94K02L Recessed Mount

General		EN 50581	
<b>Supported products</b>	AXIS P32-V/-LV Series AXIS P33-V/-LV Series AXIS Q35-V/-LV Series	<b>Dimensions</b>	Height: 123 mm (4 27/32 in) Cover ring ø 196 mm (7 23/32 in) Ceiling tile hole ø 168 mm (6 5/8 in)
<b>Mounting</b>	Recessed in ceiling tiles	<b>Weight</b>	700 g (1.54 lb)
<b>Casing</b>	Enclosure: Chromated aluminum alloy in natural color Cover ring: High-impact engineering polymer in white NCS S 1002-B	<b>Included accessories</b>	Installation Guide, drill template, Gasket C M20, kit for changing between compatible cameras
<b>Sustainability</b>	PVC free	<b>Optional accessories</b>	AXIS Safety wire 3m
<b>Environment</b>	Indoor	<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Cable routing</b>	Back: Cable conduit holes 1/2" and 3/4"	<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>	
<b>Approvals</b>	IEC/EN 60950-1 IEC/EN 60950-22		