

AXIS Camera Station S9201 Desktop Terminal

All-in-one solution for optimal viewing

AXIS Camera Station S9201 Desktop Terminal is a compact all-in-one desktop terminal designed for optimal viewing of high-definition surveillance video where space is limited. The terminal is preloaded with AXIS Camera Station software to minimize installation time and complements AXIS S1032 or AXIS S1048 rack servers to create a high performing surveillance workstation. AXIS S9201 has validated hardware and software components for optimal surveillance experience, and includes three-year hardware warranty with on-site replacement service. AXIS S9201 includes a 22 inch monitor for system overview, as well as a universal keyboard and a computer mouse.

- > **Ease of installation**
- > **AXIS Camera Station software included**
- > **22 inch monitor included**
- > **Validated hardware**
- > **On-site replacement service**



AXIS Camera Station S9201 Desktop Terminal

Processor	Intel® Core™ i3-7100, 3,9 GHz, 3MB Cache, 2C/4T	Mounting option	VESA 100 x 100 mm (3 15/16 x 3 15/16 in)
Memory	8GB (1x8GB) SO-DIMM 2400 MHz DDR4, non ECC	Operating conditions	0 °C to 35 °C (32 °F to 95° F) Humidity 20–80% (non-condensing)
Storage	M.2 128 GB SATA Solid State Drive	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Monitor	21.5" IPS Wide Viewing Angle WLED Full HD 1920x1080 resolution with anti-glare coating	Approvals	FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KCC KN32 Class B, KN35, EN 62311, EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EAC, BSMI, EN 50564, EN 62623, IEC/EN/UL 60950-1
Graphic card	Intel® HD Graphics 630	Dimensions	Monitor: 363 x 528 x 609 mm (14.3 x 20.8 x 2.4 in) Stand: Adjustable x 257 x 225 mm (Adjustable x 10.1 x 8.9 in)
Operating system	Microsoft Windows 10 IoT 2016 LTSB	Weight	Monitor: 6.32 kg (13.90 lb) Stand: 2.79 kg (6.14 lb)
Video streaming	Built-in monitor: Live view and playback: Up to 25 camera split views or 1 x 1080 camera view External monitor: Supports up to 4K	Included accessories	Installation guide, height-adjustable stand, keyboard (international/US), power cable, computer mouse, mousepad
General		Optional accessories	AXIS T8310 Video Surveillance Control Board
Power	155 W AC Input 90–264 V, 50/60 Hz	Warranty	Axis 3-year warranty, see www.axis.com/warranty
Connectors	2x USB 3.0 (side) 2x USB 3.0 (rear) 2x USB 2.0 (rear) 1x RJ45 Ethernet 1x HDMI 1.4 1x Display Port 1.2 1x UAJ (Universal Audio Jack) 1x Audio line out		

AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on www.axis.com

Environmental responsibility:
www.axis.com/environmental-responsibility