

AXIS M3206-LVE Network Camera

Robust wide-angle surveillance in 4 MP with IR

AXIS M3206-LVE offers a wide-angle view in 4 MP for indoor and outdoor surveillance. This robust, IK10-rated fixed dome includes a weathershield and mounting bracket for easy installation. Featuring WDR and built-in IR illumination it delivers clear and sharp video even in challenging light or complete darkness. Devices can be connected to the I/O ports to trigger alarms or actions, and the input can be supervised. Plus, you can connect the HDMI port to a monitor for public viewing. Furthermore, Zipstream enhanced with H.264 or H.265 significantly lowers bandwidth and storage requirements.

- > **4 MP video quality**
- > **WDR and IR illumination**
- > **Wide-angle horizontal and vertical FOV**
- > **I/O connectivity**
- > **Zipstream and support for H.264/H.265**



AXIS M3206-LVE Network Camera

Camera		Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap Overlay text, external output activation
Image sensor	1/2.5" progressive scan RGB CMOS	
Lens	2.9 mm, F2.0 Horizontal field of view: 105° Vertical field of view: 79° Fixed iris, IR corrected	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.22 lux at 50 IRE, F2.0 B/W: 0.05 lux at 50 IRE, F2.0 0 lux with IR illumination on	
Shutter time	1/32500 s to 1/5 s	
Camera angle adjustment	Pan ±175°, tilt 70°, rotation ±180°	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) High and Main Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	2304x1728 to 320x240	
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 and H.265 HDMI	
Multi-view streaming	2 individually cropped out view areas	
HDMI output	HDMI 1080p (16:9) @25/30 fps (50/60 Hz) HDMI 720p (16:9) @50/60 fps (50/60 Hz)	
Image settings	Compression, color saturation, brightness, sharpness, contrast, white balance, day/night threshold, exposure control (including automatic gain control), WDR up to 115 dB depending on scene, fine tuning of low-light behavior, text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format	
Pan/Tilt/Zoom	Digital PTZ	
Audio		
Audio input/output	Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP ^b , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTPC, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, MQTT, Syslog	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.	
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
Event conditions	Analytics, external input, supervision of input, edge storage events, virtual inputs through API	
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email	
Data streaming	Event data	
Built-in installation aids	Pixel counter, OptimizedIR with adjustable IR illumination intensity	
General		
Casing	IP66- and NEMA 4X-rated, IK10 impact-resistant polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: White NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.	
Mounting	Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread	
Sustainability	PVC free	
Memory	1024 MB RAM, 512 MB Flash	
Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 12.5 W, typical 4.2 W	
Connectors	RJ45 10BASE-T/100BASE-TX PoE HDMI type D I/O: 4-pin 2.5 mm (0.098 in) terminal block for 1 supervised digital input and 1 digital output (12 V DC output, max. load 25 mA) Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology	
IR illumination	Power-efficient, long-life 850 nm IR LEDs Range of reach 20 m (65 ft) or more depending on the scene	
Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	-40 °C to 50 °C (-40 °F to 122 °F) Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN 62471, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10, IEC/EN 60529 IP66, NEMA 250 Type 4X Network NIST SP500-267	
Dimensions	Without weathershield: Height: 104 mm (4.06 in) Ø 149 mm (5.87 in)	
Weight	With weathershield: 720 g (1.6 lb)	
Included accessories	Installation guide, Windows [®] decoder 1-user license, drill template, Resistor [®] T20 L-key, terminal block connectors, cable gaskets, connector guard, weathershield	
Optional accessories	AXIS TP3201/AXIS T94M02L Recessed Mount Kits (indoor/outdoor), AXIS T94K01D/AXIS T94T01D Pendant Kits (indoor/outdoor), AXIS TP3101 Pendant Wall Mount (indoor), AXIS Dome Intrusion Switch C, AXIS ACI Conduit Adapters, AXIS T6101 Audio and I/O Interface, AXIS T6112 Audio and I/O Interface, Axis mounts and microphones, smoked dome, black casing For more accessories, see axis.com	

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	Environmental responsibility: axis.com/environmental-responsibility
Warranty	5-year warranty, see axis.com/warranty	