

# AXIS Camera Station S9101 Mk II Desktop Terminal

## Compact client for server installations

AXIS Camera Station S9101 Mk II Desktop Terminal is a complement to Axis recorders to enable quick setup of a surveillance workstation. The terminal is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9101 Mk II has validated hardware and software components for optimal surveillance experience and includes a 5-year warranty.

- > [Ease of installation](#)
- > [AXIS Camera Station software included](#)
- > [Validated hardware](#)
- > [Extensive support](#)



# AXIS Camera Station S9101 Mk II Desktop Terminal

## Hardware

<b>Processor</b>	Intel® Pentium®
<b>Memory</b>	8 GB
<b>Graphic card</b>	Intel® UHD Graphics
<b>Power</b>	Max 60 W 100 - 240 V AC, 1.8 A, 50/ 60 Hz 12 V DC, 5 A External power adapter
<b>Connectors</b>	<b>Front side:</b> 2x USB 3.1 1x Audio line in 1x Audio line out <b>Rear side:</b> 2x USB 3.1 1x Ethernet (RJ45) 1 GbE 2x DisplayPort™ 1.2

## Video

<b>Video streaming</b>	<p>Live view streaming: 4K monitor in one of the following split scenarios: 1 stream at 4K resolution at 30 fps 4 streams at 1080p resolution at 30 fps 9 streams at 720p resolution at 30 fps 24 streams at 360p resolution at 15 fps With an additional 1080p monitor connected, the frame rates might need to be adjusted. Supports all AXIS Camera Station split scenarios</p>
------------------------	--

## Playback (one 4K monitor):

Supports the same split scenarios as live view streaming

## General

<b>Operating system</b>	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 128 GB SSD
<b>Operating conditions</b>	0 °C to 35 °C (32 °F to 95 °F) Humidity 5–95% RH (non-condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Approvals</b>	EMC EN 55032, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B, VCCI Class B Safety IEC/EN/UL 60950-1, IEC/EN/UL 62368-1
<b>Dimensions</b>	207 x 43 x 207 mm (8.15 x 1.7 x 8.15 in)
<b>Weight</b>	1.8 kg (4 lb)
<b>Optional accessories</b>	Axis joysticks and control boards For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)