


BOSCH

Invented for life

DLA-AIOU0 1200 Series IP Video Storage Appliance



- ▶ **All-in-one recording solution for up to 32 channels**
- ▶ **Pre-installed, pre-configured IP storage solution**
- ▶ **4 TB (4 x 1 TB) storage capacity**
- ▶ **Redundant dual Gigabit Ethernet network interface ports**
- ▶ **Dedicated storage operating system delivers robust, secure operation**
- ▶ **Field-replaceable hard drives**
- ▶ **Remote monitoring via desktop application or browser**

The 1200 Series IP Video Storage Appliance is an affordable, simple and reliable all-in-one recording management solution for network surveillance systems of up to 32 cameras. Powered by Bosch VRM (Video Recording Manager) software, the 1200 Series is an intelligent IP storage device that eliminates the need for separate NVR (Network Video Recorder) server and storage hardware, reducing the total cost of ownership by as much as 45%.

System Overview

The 1200 Series IP Video Storage Appliance utilizes an energy efficient, embedded design which reduces possible points of failure and boasts Bosch quality through-and-through. Utilizing “surveillance-rated” hard drives, redundant Gigabit Ethernet network interfaces, 4 GB system memory and an Intel® Pentium Dual Core Processor, the DLA 1200 Series delivers high-end performance at a very affordable price.

Simple to install, the DLA 1200 Series features wizard-based set-up and centralized configuration to reduce installation times by as much as 50%. All components are pre-installed and pre-configured. Simply connect to the network and power the unit up—the 1200 Series is ready to begin recording straight out of the box.

Adding our free BVIP Lite Suite viewing software turns the 1200 Series into a complete, ultra-low cost 16 channel IP video management solution. If more channels are required, simply add a 16 channel Viewer upgrade (VIDOSLV16UPG) to expand the system to 32 channels. And for more storage capacity, just add additional DLA 1200 Series IP Video Storage Appliances.

Functions

The silent running 1200 Series features a single-socket-system, server-class motherboard, and field-replaceable SATA II hard drives providing 4 TB of gross storage capacity. All system software is pre-installed and pre-activated—creating an out-of-the-box ready-to-use recording appliance.

The DLA 1200 Series utilizes Microsoft Windows Storage Server 2008. Windows Storage Server is a proven operating system platform that has been specifically optimized for storage applications. The Microsoft implementation of iSCSI is a reference in the industry. It delivers the highest possible quality and reliability, and is a field-proven technology installed on millions of servers worldwide.

This next generation of Windows Storage Server is focused on providing a secure platform:

- Hardened platform with reduced high risk layers
- Prevent abnormal activity in the file system and registry
- Re-architected platform to reduce corruption and compromise of the system
- Windows Service Hardening
- Windows Firewall with Advanced Security
- Enhanced and improved TCP/IP Stack

Windows Storage Server is a **dedicated OS** for Storage that has a significantly reduced attack surface than a normal Windows Server. It does not run any exposed applications like email, browser or media player and has a reduced set of services.

Management

Microsoft Windows Storage Server 2008 provides a simple, intuitive user interface for system configuration and unified storage appliance management. Administrators and IT professionals will appreciate the ability to manage the Bosch 1200 Series using the built-in Microsoft System Center Suite. The ability to use one central tool for configuration and operations management reduces installation and training requirements, and helps keep ongoing system management costs low.

Monitoring

The 1200 Series provides SNMP support, Remote Desktop support and HTTP monitoring support for the Bosch VRM recording management application and the system’s hardware. Increased reliability of high-availability hardware, embedded design as well system-wide monitoring and management ensure maximum uptime.

Bosch Quality

Bosch subjects all its products to the most comprehensive and rigorous battery of quality endurance tests in the industry. Our recording products are subjected to extreme temperatures, voltages and vibrations to determine true operating limits, so you can be assured of years of reliable operation. And Bosch firmly stands behind every product it sells with an end-to-end 3 year warranty backed by technical support.

Certifications and Approvals

Region	Certification
Europe	CE DLA-AIOUO 1200 Series

Installation/Configuration Notes

The 1200 Series comes pre-configured in a JBOD standard configuration with 1 LUN per hard drive and provides the following specifications:

Gross Capacity	Net Capacity	Bandwidth	iSCSI Sessions
4 x 1 TB	3624 GB	150 Mbit/s	32+

These values refer to the Bosch recording applications; 32+ concurrent iSCSI sessions indicate the number of concurrent recording sessions plus 4 sessions for replay. The 1200 Series may be upgraded once with an additional 32 channel license which has to be purchased. The upgrade allows for 64+ sessions: 64 sessions for recording, 4 sessions for replay.

Note The 1200 Series is an all-in-one recording solution and does not include any video management or viewing application. Video management or viewing software must be installed on separate hardware.

Note Bosch is not liable for system failures of DLA 1200 Series units without internal hard drives (available in the Asia-Pacific-Region only).

Parts Included

Processor

Processor	Intel® Pentium G6950 Dual Core (3M Cache, 2.8 GHz)
Socket	1
Cache memory	1 x 3 MB Level 2 cache
Memory protection	ECC Unbuffered
Max front side bus	1333 MHz

Memory

Memory Installed	4 GB, DDR3-1333 ECC UNB (2 x 2 GB)
------------------	------------------------------------

Storage

Storage Type	4 Trays: 3.5-inch SATA
Hard Drives Installed	4 TB, WD 1.0 TB 7.200 RPM 32 M 3.5"
Storage Controller	Embedded SATA RAID

Technical Specifications

Electrical

120 VAC Input	
Actual output wattage from power supply	170.52 W
Efficiency of power supply	85%
Total system power consumption	200.61 W
Total BTU/h	684.70
Power Factor	.98
System AC input VA requirement	204.71 VA

Electrical

240 VAC Input

Actual output wattage from power supply 170.52 W

Efficiency of power supply 86%

Total system power consumption 198.28 W

Total BTU/h 676.74

Power Factor .92

System AC input VA requirement 206.54 VA

The 1200 Series comes fully loaded and fully functional with Microsoft Operating System and Bosch recording application pre-installed

Mechanical

Form Factor Mid-Tower (731D-300)

Power Supply 300 W high efficiency

USB Ports 2 USB 2.0: 2 in rear, (1 Type-A Onboard)

Network Dual Intel® 82573 Gigabit LAN

Dimensions (H x W x D) 425 x 363 x 183 mm (16.75 x 14.25 x 7.25 in)

Weight 10.8 kg (23.8 lb)

Environmental

Operating Temperature +10 °C to +35 °C (+50 °F to +95 °F)

Non-operating Temperature -40 °C to +70 °C (-40 °F to +158 °F)

Operating Relative Humidity 8 to 90% (non-condensing)

Non-Operating Relative Humidity 5 to 95% (non-condensing)

Ordering Information**DLA-AIOUO-04AT**

1200 Series IP Video Storage System, 4 x 1 TB

DLA-AIOUO-04AT**DLA-AIOUO-000N**

1200 Series IP Video Storage System, Empty Chassis (Asia-Pacific-Region only)

DLA-AIOUO-000N**DLA-XVRM-032**

AIO-upgrade license for 32 cameras (e-license)

DLA-XVRM-032**Accessories****DLA-UDTK-100A**

1000 GB HDD

DLA-UDTK-100A

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

Represented by