D122L Dual battery harness, 35", 12V

www.boschsecurity.com





- ▶ Used for batteries in parallel in a separate enclosure
- ▶ Slide-on connectors
- ▶ Built-in circuit breaker protection

Use the D122L Dual battery harness with long leads when batteries are in a separate enclosure from the control panel. It protects the installer and battery when connecting two batteries, in parallel, to compatible control panels. The D122L eliminates the hazards of batteries connected in parallel by utilizing a thermal circuit breaker to govern the circuit. It breaks the electrical circuit of the second battery when the thermal rating is exceeded.

Certifications and approvals

Region	Regulatory compliance/quality marks	
USA	UL	Suitable for use with Bosch's B Series and G Series UL Listed products/accessories
	CSFM	see the Bosch website (www.boschsecurity.com)

Parts included

Quantity	Component
1	Battery harness
1	Hardware pack – 4 locknuts, 4 screws, 4 battery contacts
1	Installation Manual

Technical specifications

Mechanical

Cable length	35 in. (89 cm)
Wire gauge	18 AWG (ISO 0.75 mm²)

Ordering information

D122L Dual battery harness, 35", 12V

Harness with circuit breaker and leads measuring 35 in. (89 cm). Connects two batteries (in parallel) to a compatible control panel in a separate enclosure. Order number **D122L**