

# D300A Photoelectric Duct Smoke Detector (24 VAC/VDC or 115 VAC)

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Conventional duct detector (D300A)
- ▶ For use with Bosch D7022 and D7024 Conventional Fire Alarm Control Panels (FACPs)
- ▶ Comes complete with a conventional photoelectric smoke detector head
- ▶ Steel sampling tube

The D300A Duct Detector is an accessory device. It comes with a photoelectric smoke detector head and a housing for use in heating, ventilation, and air conditioning (HVAC) duct works. The D300A can be powered by 24 VAC, 24 VDC, or 115 VAC. Use the provided output terminals for remote accessories such as remote status indicators and reset key switches or push buttons.



**Notice**

Do not use the D300A for open-air detection.



**Notice**

Refer to NFPA 90A and NFPA 72 for more information on the operation and installation of duct smoke detectors.

## Functions

### Air Sampling

A tube that protrudes into the duct samples the air through positive pressure to the detector head. An exhaust tube of one standard length is supplied in the

installation kit with the duct detector housing unit. Once the duct width is determined, order the air sampling tube(s). Sampling tubes come in three standard lengths and can be cut to size to fit the duct.

## Certifications and approvals

Region	Certification	
USA	UL	ULROX: Smoke - Automatic Fire Detectors (UL268 and A)
	CSFM	3240-1615:0167
Hong Kong	HKFSD	

## Installation/configuration notes

### Compatible Products

The following products are compatible with the D300A and D300A-HV Photoelectric Duct Smoke Detectors:

Category	Product ID	Product Description
Control Panels	D7022	Two-zone FACP
	D7024	Conventional FACPs

	D7024-EXP	Conventional FACPs for export
Detector Head	D282A-DH	Replacement duct smoke detector head

### Installation Considerations

Use the D300A detector in HVAC ducts with air velocities from 300 ft/min to 4000 ft/min (90 m/min to 1.2 km/min). Verify air velocity by checking the duct installation specifications, or by using an Alnor Model 6000P velocity meter or its equivalent.

Install the D300A in ducts ranging from 1 ft (0.3 m) to 10 ft (3 m) in diameter. To verify the correct sampling of air in the duct, use a Dwyer Model 4000 differential pressure gauge or its equivalent.

### Mounting

#### Notice

To prevent false alarms, do not mount the duct detector in areas of extreme high or low temperature, high humidity, or where duct air might contain gasses or excess dust. See NFPA 90A, 72 and 101.

A mounting template and four sheet metal screws are packaged in the installation kit. Attach the template to the duct at the desired place. Drill or punch and clean the holes. Sampling tube connectors have set screws preventing mounting in the wrong airflow direction.

### Wiring

Wire the detectors according to the engineering drawings. The terminals can use for wire up to 14 AWG (1.8 mm).

## Technical specifications

### Electrical

#### Current

Alarm:	24 VAC: 95 mA 24 VDC: 60 mA 115 VAC: 28 mA
--------	--

Standby:	24 VAC: 20 mA 24 VDC: 13 mA 115 VAC: 14 mA
----------	--

#### Voltage

Input:	24 VAC/VDC, or 115 VAC
--------	------------------------

### Relay Contacts

Rating	10 A maximum resistive
--------	------------------------

### Environmental

Relative Humidity:	10% to 85%, non-condensing
Temperature (operating):	+32°F to +120°F (0°C to +49°C)

### Mechanical

Duct Air Velocity:	300 ft/min to 4000 ft/min (90 m/min to 1.2 km/min)
--------------------	--

### Trademarks

Trademark names are used throughout this document. In most cases, these designations are claimed as trademarks or registered trademarks in one or more countries by their respective owners. Rather than placing a trademark symbol in every occurrence of a trademark name, Bosch Security Systems, Inc. uses the names only in an editorial fashion and to the benefit of the trademark owner with no intention of infringing the trademark.

Alnor is a registered trademark of TSI Incorporated.

Dwyer is a trademark of Dwyer Instruments, Inc.

## Ordering information

### D300A Photoelectric Duct Smoke Detector (24 VAC/VDC or 115 VAC)

Photoelectric smoke detector head that can be powered by 24 VAC, 24 VDC, or 115 VAC and a housing for use in heating, ventilation, and air conditioning (HVAC) duct works.

Order number **D300A**

### Accessories

#### D304 Remote Annunciator Plate

Brushed stainless steel annunciator plate with a red alarm LED and a green Pilot LED

Order number **D304**

#### D305 Remote Test/Reset Annunciator Plate

Brushed stainless steel annunciator plate; red alarm LED; green Pilot LED; key-operated Test/Reset switch

Order number **D305**

#### FAA-325-2.5 Sampling Tube (2.5 ft)

2.5 ft (762 mm) long sample tube for use with the FAD-325 and FAD-325-R Analog Duct Detectors

Order number **FAA-325-2.5**

#### FAA-325-5 Sampling Tube (5 ft)

5 ft (1.52 m) long sample tube for use with the FAD-325 and FAD-325-R Analog Duct Detectors

Order number **FAA-325-5**

#### FAA-325-10 Sampling Tube (10 ft)

10 ft (3.05 m) long sample tube for use with the FAD-325 and FAD-325-R Analog Duct Detectors

Order number **FAA-325-10**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com