

DIVAR IP 3000

www.boschsecurity.com



BOSCH
Invented for life



- ▶ All-in-one, fully featured video management solution for up to 32 channels
- ▶ Out-of-the-box IP video recording solution with up to 8 TB (4 x 2 TB) storage capacity
- ▶ Robust, secure operation – instant real time access to video
- ▶ Instantly find what you are looking for
- ▶ Advanced user and alarm management

The DIVAR IP 3000 appliance is an affordable and easy to use all-in-one recording, viewing, and management solution for network surveillance systems of up to 32 channels (all channels pre-licensed). Running the full Bosch Video Management System solution and powered by Bosch Video Recording Manager including the Video Streaming Gateway to integrate 3rd party cameras, DIVAR IP 3000 is an intelligent IP storage device that eliminates the need for separate NVR (Network Video Recorder) server and storage hardware. Thus, reducing the total cost of ownership by as much as 45% and providing both, a professional video management system solution and ease of operation.

DIVAR IP 3000 is a 4-bay mini tower unit that combines advanced management and state-of-the-art recording management into a single cost-effective, plug and play IP recording appliance for IT-minded customers which are seeking for a state-of-the-art “second generation” DVR and NVR recording solution.

System overview

The DIVAR IP 3000 appliance utilizes a highly energy efficient, embedded design at a very affordable price which nevertheless boasts Bosch quality through-and-through.

Easy to install and operate, DIVAR IP 3000 features wizard-based set-up and centralized configuration to reduce installation times by as much as 45%. All components are pre-installed and pre-licensed. Simply connect to the network and power the unit up – DIVAR IP 3000 is ready to begin recording straight out of the box.

Bosch Video Management System manages all IP and digital video and audio, plus all the security data being transmitted across your IP network. It seamlessly combines IP cameras and encoders, provides system-wide event and alarm management, system health monitoring, user and priority management.

Functions

DIVAR IP 3000 features front-swappable SATA-II hard drives providing up to 8 TB of gross storage capacity. All system software is pre-installed and pre-activated –

creating an out-of-the-box ready-to-use video management appliance. DIVAR IP 3000 utilizes Microsoft Windows Storage Server 2008 R2 (64-bit).

Instant real time access to video

View high quality HD video despite low or limited bandwidth connections. Dynamic Transcoding technology ensures you can view your video immediately – anytime, anywhere.

Dynamic Transcoding retrieves the data from DIVAR IP 3000 and subsequently decodes and decompresses the data stream to a lower rate bit stream tailored to the bandwidth of the connection. When the video is paused, the instant detail enhancement feature instantly displays the full HD video.

Management

Once booted up the system will offer immediate access to the Bosch Video Management System management application via a customized GUI. The ability to use one central GUI for configuration and operations management reduces installation and training requirements, and helps keep ongoing system management costs low.

Bosch quality

Bosch subjects all its products to the most comprehensive and rigorous battery of quality endurance tests in the industry. Our recording products are subjected to extreme temperatures, voltages and vibrations to determine true operating limits, so you can be assured of long-term reliable operation. And Bosch firmly stands behind every product it sells with an end-to-end 3 year warranty backed by technical support.

Certifications and approvals

Region	Certification
Europe	CE DIVAR IP 2000/3000

Installation/configuration notes

DIVAR IP 3000 comes pre-configured in a standard non-RAID configuration and provides the following specifications:

Gross capacity	Net capacity	Bandwidth (read & write)	Cameras
w/o HDD	n/a	120 Mbit/s	32
2 x 2 TB	3700 GB	120 Mbit/s	32
4 x 2 TB	7400 GB	120 Mbit/s	32

These values refer to the system with all supported Bosch CCTV applications installed and running; net capacity for a non-RAID configuration; 32 connected cameras indicate the number of concurrent recordable cameras including the connected replay clients.

The DIVAR IP 3000 appliance allows a maximum of overall 32 channels: recording and replay clients. The system is re-configurable to a RAID-1 configuration with reduced performance and net capacity values. For the standard systems please note the number of pre-installed licenses and the upper limit of each:

	Pre-installed licenses	Upper limit
Workstation clients	5	5
DVR/BRS systems	1	5
CCTV keyboards	1	5
Forensic Search clients	5	5
Mobile video service client	1	1

For further information, under **Ordering information** see **Software Options**.



Notice

Bosch is not liable for system failures of units equipped with non-Bosch hard drives if the non-Bosch hard drives are source of the issues.

Parts included

Processor	
Processor	Intel i3-2120 processor
Socket	1 x (Intel processor socket LGA1155)
Chipset	Intel Core logic chipset PCH Cougar Point C206
Memory	
Memory type	DDR3 1066/1333 MHz UDIMM
Max front side bus	1333 MHz
Memory installed	4 GB, DDR3-1333 SO-DIMM (2 x 2 GB)
Storage	
Storage type	4 trays: 3.5-inch SATA
Hard drives installed	4 x HDD (2 TB 5400RPM GP) max
Graphics	1 x USB DVI port, onboard graphics VGA port
Network	1 x 1 GbE RJ45 port

System status

DIVAR IP 3000 family comes fully loaded and fully functional with Microsoft Operating System and Bosch application pre-installed: WSS 2008 R2, 64-bit; Bosch Video Management System; Bosch Video Recording Manager including Video Streaming Gateway; Dynamic Transcoding.

ONVIF support restrictions

Event-based recording is not supported

Audio on some 3rd party cameras is not fully supported, which may result in non-availability of audio streams

TCP is not supported for ONVIF cameras but with UDP protocol only

Motion JPEG is not supported

VCA is always recorded for Bosch devices

VCA is not available for ONVIF cameras

Technical specifications

Electrical

Power supply	220 W (100/240 VAC)
Energy efficiency	Energy Star compliant power supply
Power consumption	82 W max 41 W idle

Mechanical

Form factor	4-bay mini tower
Power supply	1 x internal power supply
USB ports	6 x USB 2.0, 1 x USB 3.0 port
Network	1 x Gigabit Ethernet LAN
Dimensions (H x W x D)	180 x 200 x 212 mm (7.09 x 7.87 x 8.35 in)
Weight	w/o HDD: 4.65 kg (10.25 lb) fully loaded: 7.35 kg (16.20 lb)

Environmental

Operating temperature	+10 °C to +35 °C (+50 °F to +95 °F)
Non-operating temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating relative humidity	8 to 90% (non-condensing)
Non-operating relative humidity	5 to 95% (non-condensing)

Ordering information

DIVAR IP 3000, 2 HDD

All-in-one recording, viewing, and management solution for network surveillance systems of up to 32 channels, 2 x 2 TB storage capacity

Order number **DIP-3042-2HD**

DIVAR IP 3000, 4 HDD

All-in-one recording, viewing, and management solution for network surveillance systems of up to 32 channels, 4 x 2 TB storage capacity

Order number **DIP-3042-4HD**

DIVAR IP 3000, w/o HDD

All-in-one recording, viewing, and management solution for network surveillance systems of up to 32 channels, w/o HDD

Order number **DIP-3040-00N**

Accessories

DIVAR IP HDD

DIVAR IP 2000/3000 – 2000 GB HDD

Order number **DIP-2302-HDD**

Software Options

DIVAR IP DVR Expansion

1 DVR expansion

Order number **MBV-XDVR-DIP**

DIVAR IP CCTV Keyboard Expansion

1 keyboard expansion

Order number **MBV-XKBD-DIP**

DIVAR IP Allegiant Matrix Connection

Allegiant license

Order number **MBV-FALG-DIP**

DIVAR IP ATM/POS Connection

ATM/POS license

Order number **MBV-FATM-DIP**

DIVAR IP OPC Server Connection

OPC server license

Order number **MBV-FOPC-DIP**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com