


# LTC 9210/01, LTC 9215/00 (S), LTC 9219/01, and LTC 9223/01 Indoor/ Outdoor Mounts




- ► Feed-through Design for Cable Management
- ► Maximum Load: 9 kg (20 lb)
- ▶ 360° Rotation, 180° Tilt
- Versatile Design
- ► Adjustable Mount Heads
- Lightweight
- ► Corrosion-resistant Finish

The LTC 9210/01, LTC 9215/00, LTC 9215/00S, LTC 9219/01 and the LTC 9223/01 feed-through mounts are indoor/outdoor mounting units designed for fixed camera, or camera housing installations with up to a 9 kg (20 lb) rated load. These models are made of lightweight aluminum and feature welded construction, providing an extremely rigid camera mount. In addition, the versatile swivel head rotates 360° and tilts 180° for maximum flexibility. The tubular feed-through design provides cable management from mounting head to mounting surface.


These mounts are compatible with the UHI Indoor Housing series and the UHO Outdoor Housing series. The LTC 9215/00S, has been designed specifically for the LTC 9480 Series housings, while the larger LTC 9215/00 and LTC 9219/01 can be used with the LTC 9480, HSG 9483, and the LTC 9488 Series camera housings. All mounts come fully assembled.




LTC 9210/01 and LTC 9223/01Column Mount




LTC 9219/01 Feed-through J-Mount



LTC 9215/00 Wall Bracket





LTC 9215/00S Short Wall Bracket

## **Technical Specifications**

# LTC 9210/01 20 mm (8 in) Indoor Outdoor

| Column Mount                                 |                 |
|--|-----------------|
| Maximum Load                                 | 9 kg (20 lb)    |
| Mounting Head Adjustable 360° pan, 180° tilt |                 |
| Finish Light gray                            |                 |
| Approx. Weight                               | 0.3 kg (0.6 lb) |

#### LTC 9215/00 30 mm (12 in) Indoor/Outdoor

| Feed-through Wall Mount                                  |                 |  |
|--|-----------------|--|
| Maximum Load   | 9 kg (20 lb)    |  |
| Mounting Head Adjustable 360° pan, 180° tilt             |                 |  |
| Finish   | Light gray      |  |
| Approx. Weight   | 0.4 kg (0.9 lb) |  |
| Accessory for LTC 9215/00 LTC 9213/01 Pole Mount Adapter |                 |  |

#### LTC 9215/00S 18 cm (7 in) Indoor/Outdoor

| Feed-through Wall Moun     | t                              |
|----------------------------|--------------------------------|
| For use with LTC 9480 S    | eries housings.                |
| Maximum Load               | 9 kg (20 lb)                   |
| Mounting Head              | Adjustable 360° pan, 180° tilt |
| Finish                     | Light gray                     |
| Approx. Weight             | 0.3 kg (0.7 lb)                |
| Accessory for LTC 9215/00S | LTC 9213/01 Pole Mount Adapter |

## LTC 9219/01 40 cm (15 in) Indoor/Outdoor

Feed-through Ceiling J-Mount

| 0 0            |                                |
|----------------|--------------------------------|
| Maximum Load   | 9 kg (20 lb)                   |
| Mounting Head  | Adjustable 360° pan, 180° tilt |
| Finish         | Light gray                     |
| Approx. Weight | 0.55 kg (1.2 lb)               |

#### LTC 9223/01 610 mm (24 in) Indoor Outdoor

Column Mount

| Maximum Load   | 9 kg (20 lb)                   |  |
|----------------|--------------------------------|--|
| Mounting Head  | Adjustable 360° pan, 180° tilt |  |
| Finish         | Light gray                     |  |
| Approx. Weight | 0.544 kg (1.2 lb)              |  |

Warning Mounts must be mounted as shown.

| Ordering Information   |              |  |  |  |
|--|--------------|--|--|--|
| LTC 9210/01 Column Mount<br>for 8-inch, 9 kg (20 lb) max load, light gray<br>finish  | LTC 9210/01  |  |  |  |
| LTC 9215/00 Wall Bracket<br>for 12-inch, 9 kg (20 lb) max load, for<br>LTC 9380 and LTC 948x series housings, feed-<br>through version, light gray finish      | LTC 9215/00  |  |  |  |
| LTC 9215/00S Short Wall Bracket<br>for 7-inch, 9 kg (20 lb) max load, for LTC 938x<br>and LTC 948x series housings, feed-through<br>version, light gray finish | LTC 9215/00S |  |  |  |
| LTC 9219/01 Feed-through J-Mount<br>for 15-inch, 9 kg (201b) max load, for LTC 938x<br>and LTC 948x series housings, light gray finish                         | LTC 9219/01  |  |  |  |
| LTC 9223/01 Column Mount<br>for 24-inch, 9 kg (20 lb) max load, light gray<br>finish   | LTC 9223/01  |  |  |  |

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security,sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Represented by
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2600
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com