

IP Camera 200 Series

www.boschsecurity.com



BOSCH

Invented for life



Advantage Line

The Bosch NBC-255-P and NBC-225-P IP cameras are ready-to-use, complete network video surveillance systems inside a compact housing. These cameras bring Bosch's high-performance technology into the realm of small office and retail businesses by offering a cost-effective solution for a broad range of applications.

The cameras use H.264 compression technology to give clear images while reducing bandwidth and storage by up to 30%.

Features

- ▶ Complete network video surveillance system
- ▶ Sharp images of moving objects
- ▶ Dual H.264 and M-JPEG streams simultaneously
- ▶ ONVIF conformant
- ▶ SD/SDHC card slot for edge recording

Technical specifications

Power	
Input voltage	+12 VDC or Power-over-Ethernet
Power consumption	3.36 W (max)
Video	
Sensor type	¼-inch CMOS
Sensor pixels	640 x 480
Sensitivity	1.0 lx
Video resolution	VGA, QVGA
Video compression	H.264 MP (Main Profile); H.264 BP+ (Baseline Profile Plus); M-JPEG
Frame rate	30/25 fps: all resolutions
Lens	
Lens type	NBC-255-P: Varifocal 2.8 to 10 mm, F1.4 to close NBC-225-P: Fixed 4.9 mm, F2.8
Lens mount	NBC-255-P: CS mount NBC-225-P: Board mounted
Connection	
Alarm input	+9 to 30 VDC
Relay out	24 VAC/VDC, 1 A
Audio	
Audio input	Built-in microphone Line in jack connector
Audio output	Line out jack connector
Audio communication	Two-way, full duplex
Audio compression	G.711
Local Storage	
Memory card slot	Supports up to 32 GB SD/SDHC card
Recording	Continuous recording, ring recording, alarm/events/ schedule recording
Software Control	
Unit configuration	Via web browser or PC surveillance software
Network	
Protocols	HTTP, HTTPS, SSL, TCP, UDP, ICMP, RTSP, RTP, RTCP, IGMPv2/v3, SMTP, FTP, DHCP client, ARP, DNS, DDNS, NTP, SNMP, UPnP
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
PoE	IEEE 802.3af compliant
Mechanical	
Dimensions with lens (H x W x D)	NBC-255-P: 55 x 72 x 178 mm (2.17 x 2.83 x 7.01 in.) NBC-225-P: 55 x 72 x 123 mm (2.18 x 2.83 x 4.84 in.)
Weight (with lens)	NBC-255-P: approx. 245 g (0.54 lb) NBC-225-P: approx. 177 g (0.39 lb)
Mounting	¼-inch mounting socket on top and bottom
Environmental	

Operating temperature Camera	0 °C to +50 °C (+32 °F to +122 °F)
Operating temperature Universal Power Supply Unit	0 °C to +40 °C (+32 °F to +104 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	10% to 80% relative humidity (non condensing)
Certifications and approvals	
Region	Certification
Europe	CE
Standards	
	EN 60950-1: 2006, Reference IEC 60950-1:2005
	UL 60950-1: 1st edition dated October 31, 2007
	CAN/CSA-C22.2 NO. 60950-1-03
	EN 50130-4:1995 + A1:1998 + A2:2003
	FCC Part15 Subpart B, Class B
	EMC directive 2004/108/EC
	EN 55022 class B
	EN 61000-3-2 :2006
	EN 61000-3-3 : 1995+A1 :2001+A2 :2005
	EN 55024
	AS/NZS CISPR 22 (equal to CISPR 22)
	ICES-003 Class B
	EN 50121-4:2006
Product certifications	CE, FCC, UL, cUL, C-tick, CB, VCCI
Power supply	CE, UL, cUL, PSE, CCC
Ordering information	
NBC-255-P IP Camera, 2.8-10mm lens	NBC-255-P
NBC-225-P IP Camera, 4.9mm lens	NBC-225-P
Accessories	
LTC 9348/00 Series Indoor Dome Housings	LTC9348/00
UHI-SBG-0 Series Indoor Housing	UHI-SBG-0
UHI-ASBG-0 Series Indoor Housing	UHI-ASBG-0

Represented by:

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:
Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:
Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com