

EX36-IP No-Grip Corner Mount Camera

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Intelligent Video Analysis (IVA)
- ▶ No-Grip Design
- ▶ High Performance Video Encoder
- ▶ Covert Active-Infrared Illumination

The EX36-IP is a No-Grip corner mount camera featuring a powerful processor for Intelligent Video Analysis (IVA) and IP Infrared Imaging design for 24/7 effective networked surveillance in high risk, vandal-prone applications.

The EX36-IP uses a No-Grip anchor-free design which enables it to view the entirety of a small room, including the floor beneath the camera, under any ambient lighting conditions, even in completely dark rooms. The camera is impossible to grip or hang from, providing maximum safety for applications such as prison cells, elevators and psychiatric hospitals.

The EX36-IP harnesses the power of infrared illumination to deliver outstanding images day or night, integrating seamlessly with existing IP network infrastructure. The EX36-IP provides outstanding day and night imaging performance with lower bandwidth network impact than standard IP cameras.

Functions

Applications

- Prison cells
- Hospital recovery rooms
- Psychiatric care rooms
- Vandal-prone areas
- Indoor CCTV

Certifications and approvals

Region	Certification
Europe	CE

Technical specifications

Video

Sensor	MX4 Hi-resolution day/night CCD	C7 Hi-resolution Color CCD
Effective Pixels (NTSC)	768 (H) x 494 (V)	768(H) x 494(V)
Effective Pixels (PAL)	752 (H) x 582 (V)	752(H) x 582(V)
Resolution	540 TVL color / 540 TVL monochrome	500 TVL
S/N Ratio	Greater than 48dB	Greater than 48dB
Daytime Sensitivity	0.02 Lux with F1.4 lens	2.7 Lux at F1.4
Night-time Sensitivity	0 Lux - operates in total darkness	2.7 Lux at F1.4
Lens	Fixed: 2.5 mm	Fixed: 2.5 mm

Gamma	0.45	0.45
Video Output	1 Vpp, 75 ohms	1 Vpp, 75 ohms
Day-Night Switching	Photocell-controlled, automatic	N/A
Infrared Illumination		
Photocell	Automatic, sensitivity adjustable	N/A
LEDs	84 LEDs, Infrared, intensity adjustable	None - No IR window
Wavelength	940 nm covert or 850 nm semi-covert	N/A
Night Vision Distance	9 m (30 ft)	N/A

Interfaces		
Ethernet	10/100 Base-T RJ45	
Analog	PAL or NTSC BNC	

IP		
Protocols	Telnet, RTP, HTTP(S), ARP, TCP, UDP, IP, ICMP, DHCP, IGMPv2/v3, SNMP, 802.1x	
Compression	MPEG-4 SP and MJPEG, up to 30 frames per second, tri-stream selectable	
Frame Rate	1-30 FPS programmable (full motion)	
Bandwidth	Configurable from 9.6 Kbps to 6 Mbps	

Resolution and Frame Rates	PAL	NTSC
4CIF: 25/30 IPS	704 x 576	704 x 480
2CIF: 25/30 IPS	704 x 288	704 x 240
half D1: 25/30 IPS	352 x 576	352 x 480
CIF: 25/30 IPS	352 x 288	352 x 240
QCIF: 25/30 IPS	176 x 144	176 x 120

Mechanical

Weight	1.2 kg (2.6 lbs)
Construction	Robust aluminum casting, painted steel with flush removable front panel and tamper-resistant screws
Window	¼-inch thick LEXAN
Overall Dimensions (WxHxD)	224 x 134 x 155 mm (8.8 x 5.3 x 6.1 in)

Environmental

Operational Range	-50°C to +50°C (-58°F to 122°F)
-------------------	---------------------------------

Electrical

Voltage Supply	12 VDC / 24 VAC
Power Consumption	900 mA at 12 VDC max

Ordering information**NEC-360F02-21W IP Corner Mount Camera**

IP vandal proof corner cam, 1/3 in. hi-res color, 500 TVL, NTSC

Order number **NEC-360F02-21W**

NEC-360F02-11W IP Corner Mount Camera

IP vandal proof corner cam, 1/3 in. hi-res color, 500 TVL, PAL

Order number **NEC-360F02-11W**

NEI-368F02-21W IP Corner Mount Camera

IP vandal proof corner cam, 1/3 in. extended day/night, 540/540 TVL, 850 nm IR, NTSC

Order number **NEI-368F02-21W**

NEI-368F02-11W IP Corner Mount Camera

IP vandal proof corner cam, 1/3 in. extended day/night, 540/540 TVL, 850 nm IR, PAL

Order number **NEI-368F02-11W**

NEI-369F02-21W IP Corner Mount Camera

IP vandal proof corner cam, 1/3 in. extended day/night, 540/540 TVL, 940 nm IR, NTSC

Order number **NEI-369F02-21W**

NEI-369F02-11W IP Corner Mount Camera

IP vandal proof corner cam, 1/3 in. extended day/night, 540/540 TVL, 940 nm IR, PAL

Order number **NEI-369F02-11W**

Accessories**UPA-2430-60 Power Supply**

120 VAC, 60 Hz, 24 VAC, 30 VA Out

Order number **UPA-2430-60**

UPA-2420-50 Power Supply

220 VAC, 50 Hz, 24 VAC, 20 VA Out

Order number **UPA-2420-50**

PSU-124-DC050 Universal Power Supply

Universal Outdoor Power Supply, 120 to 240 VAC, 50/60 Hz In; 24 VDC, 50 W Out

Order number **PSU-124-DC050**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com