



- OPTIONS:**
- PDTDS22F (FIXED)
 - PDTDS22R (REMOVABLE)
- CAP STYLE: **SEE NOTES****
- 

FLAT CAP



DOME CAP
- FINISH:**
- POWDER COAT RAL# _____
 - GALVANIZED
 - OTHER _____

- NOTES:**
- 1.) CONCRETE PER ASTM STANDARD. SPECIFICATIONS TO BE PROVIDED WITH INSTALLATION DETAILS.
 - 2.) REINFORCING STEEL SHALL MEET ASTM STANDARD FOR WELDED WIRE REINFORCEMENT.
 - 3.) COMPACTED BACKFILL PER ASTM STANDARD. SPECIFICATIONS TO BE PROVIDED WITH INSTALLATION DETAILS.
 - 4.) FOR REBAR CONFIGURATION DIMENSIONS REFER TO SHEET 2.
 - 5.) CAP STYLE OPTIONS ONLY AVAILABLE FOR PDTDS22-FIXED. STAINLESS STEEL AND PLASTIC COVERS ARE AN ADDITIONAL OPTION AVAILABLE FOR PDTDS22-REMOVABLE.
 - 6.) PDTDS22-FIXED CAPS WILL BE SENT SEPERATLY TO ALLOW BOLLARD TO BE FILLED WITH CONCRETE. CAPS WILL HAVE REBAR WELDED TO THE UNDERSIDE FOR ANCHORING INTO THE CONCRETE AFTER BOLLARD HAS BEEN FILLED. DOME CAP OPTION WILL ADD APPROX. 2" TO OVERALL HEIGHT.

Company: _____

Project Name: _____

Signee's Name Written Clearly: _____ Date: _____

Authorized Signature: _____

SIZE B	PRODUCED BY :	JMG	REV :	REV. A 9/4/14
	PRODUCED ON :	5/30/14	SHEET :	1 OF 2



**19440 S. DOMINGUEZ HILLS DR.
RANCHO DOMINGUEZ, CA 90220**

**www.CalPipeBollards.com
562.803.4388 Direct
562.803.9885 Fax**

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
CALPIPE INDUSTRIES INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
CALPIPE INDUSTRIES INC. IS PROHIBITED

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ± 1/4
ANGULAR: MACH ± 1 BEND ± 1
TWO PLACE DECIMAL THREE ± 0.010
PLACE DECIMAL ± 0.005

**PDTDS22F/R
M50/K12 FIXED & REMOVABLE**