

**3203/RI****ROMA SERIES AUDIO/VIDEO ENT. PANEL FOR IKALL UNIT, 3  
BUTTONS**

Video entry phone entrance panel with front plate in 3 mm thick watchmaking brass plate with PVD treatment. Complete with flush-mounted box and anti-intrusion screws. All entrance panels are fitted with bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39. The keypad should be finished with an audio/video unit depending on the wiring system used. 3 buttons, 1 wire. Plate dimensions 135x293x3 mm. Box dimensions 115x227x55 mm. 1 bulb socket



**3203/RI**

**ROMA SERIES AUDIO/VIDEO ENT. PANEL FOR IKALL UNIT, 3  
BUTTONS**

Flush-mounted

Yes



3203/RI

## ROMA SERIES AUDIO/VIDEO ENT. PANEL FOR IKALL UNIT, 3 BUTTONS



### **3063D**    **MODULE W/8 BUTT.IN 2 ROWS+VIP FOR SING.-PLATE PAN.**

Button management module. Works in conjunction with audio/video modules or audio module. Allows management of 8 buttons.  
Dimensions: 45x55x30 mm.



### **1172B**    **LED BULB FOR EXTERNAL UNITS**

LED bulb for nameplate lighting.



### **1621**    **Simplebus 2W audio unit with LED, Ikall series**

Speaker unit for 2-wire systems complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming calls to users. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.



### **4681**    **2 WIRES AUDIO/VIDEO UNIT**

Colour audio-video unit for 2-wire systems with terminal block complete with directable colour camera with front adjustment, LED camera lighting. Complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming calls to users. Programmable audiovisual functions for users with disabilities. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.

**3203/RI****ROMA SERIES AUDIO/VIDEO ENT. PANEL FOR IKALL UNIT, 3  
BUTTONS****1621VC 2 WIRES IKALL AUDIO UNIT FOR REMOTE CAMERA**

Speaker unit for 2-wire systems complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Allows use of external PAL colour cameras. Complete with microprocessor and 8-position dip switch for programming calls to users. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.

**1622VC 2 WIRES IKALL AUDIO UNIT FOR REMOTE CAMERA**

Module which allows modulation and transmission of the colour video signal on the riser. On input it has the composite video signal of a colour camera. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.