316

1/5



#### 3454HD/A

# STAINLESS STEEL 316 TOUCH A/V ENTRANCE PANEL, VIP





Stainless steel flush-mounted entrance panel (fitted level with the wall) with 8" capacitive touch-screen featuring high visibility and impact-proof glass. IK08 certification. Operation with configurable graphics (list of names with search, virtual static buttons up to 10 users, alphabetised directory, number code up to 8 digits). Allows customisation of the virtual buttons and viewing of general apartment block messages. Fully configurable via ViP Manager software. Fitted with RFID reader for local door lock control, an additional relay for various uses and proximity and brightness sensors for optimal operational management. Complete with H.264 compatible audio/video unit art. 4682HD and flush-mounted box with concealed fixing screws. Power supply 33VDC with art. 1596B. Plate dimensions (W x H x D): 182x342x3x3 mm. ViP system. Compatible with H.264 video format.

## **AWARDS**











316



## 3454HD/A

STAINLESS STEEL 316 TOUCH A/V ENTRANCE PANEL, VIP
---

GENERAL DATA	
Туре	Monoblock
Height (inch) (pc)	80.79
Width (inch) (pc)	42.99
Depth (inch) (pc)	10.63
Product weight (oz) (oz)	141.1
Product color	Steel
Flush-mounted	Yes
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Compatible audio and audio/video units	Art.4682HD
ViP	Yes

DISPLAY	
Display type	Graphic LCD
Display size (")	8
Touch screen	Yes, capacitive
Resolution (pixel)	1280x720

AUDIO FEATURES	
Microphone	9.7 (ø), omnidirectional
Loudspeaker	50mm (Ø), 8 Ohm, 0.2W
Technologies implemented	Echo canceling

CAMERA FEATURES	
Camera	Colors
Sensor type	1/2.9" CMOS
Lens optical dimensions (pc)	0.66
Angle of view (H x V - °)	83 x 67
Video resolution (H x V - pixel)	1280 x 720



### 3454HD/A

# STAINLESS STEEL 316 TOUCH A/V ENTRANCE PANEL, VIP

## **CAMERA FEATURES**

Video compression H.264

316

ELECTRICAL CHARACTERISTICS	
Type of power supply	External power supply
Supply voltage	33VDC
Absorption in stand-by (W)	13
Maximum absorption (W)	16

HARDWARE FEATURES	
Call type	Push-buttons, Digital
Type of buttons	Capacitive
Number of push-buttons (n°)	60
Clamps	TX+ TX- RX+ RX- V+ V-/GND SE L L RTE DO GND NC COM NO
Removable terminals	Yes
Number of inputs (n°)	2
Number of outputs (n°)	1
Integrated proximity reader	RFID Mifare Classic
Communication ports	RS485
Proximity sensor	Yes
Brightness sensor	Yes

NETWORK AND COMMUNICATION PROTOCOLS	
Type of LAN network	Ethernet 10 Mbit/s
IP address assignment	Auto IP, DHCP, Static

PROGRAMMING MODE	
ViP Manager software	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating	IP54



### 3454HD/A

# STAINLESS STEEL 316 TOUCH A/V ENTRANCE PANEL, VIP

## **ENVIRONMENTAL AND COMPLIANCE FEATURES**

316

Vandal Resistant rating (IK code)	IK08
Operating temperature (°F) (°F)	-13 ÷ 131
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS	
Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Access control via proximity reader	Yes
Access control via door opener code	Yes
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes
Customizable welcome message	Yes

GENERAL FEATURES	
Type of finishing materials	Stainless steel AISI 316
Customizable screensaver	Yes



### 3454HD/A

# STAINLESS STEEL 316 TOUCH A/V ENTRANCE PANEL, VIP

### **ACCESSORIES**



## 3462/6 WALL HOUSING FOR 30NE6 ANALOG, TOUCH, SENSE

Stainless steel accessory for wall-mounted entrance panels 30NE6 ANALOG, 30NE6 TOUCH (art. 3453S, 3453S/A, 3454HD, 3454HD/A), 30NE6 SENSE (art. 3451S, 3451AS, 3452HD). Dimensions 180x340x56 mm



## 3460/6 FLUSH-MOUNT BOX FOR 30NE6 ANALOG, TOUCH, SENSE

Flush-mounted box for 30NE6 ANALOG, 30NE6 TOUCH (art. 3453S, 3453S/A, 3454HD, 3454HD/A), 30NE6 SENSE (art. 3451S, 3451AS, 3452HD). Dimensions: 164x323x56 mm



#### 3458 ACCESS CONTROL ACCESSORY MODULE FOR EXTERNAL UNITS, 316

Flush-mounted 3 mm thick stainless steel plate for housing the access control module. Can be used in conjunction with all entrance panels in the 316 range. Dimensions 88x182x3 mm