UNIFY CWE-U320

BY) (cellgate

CELLULAR WIEGAND ENTRY SYSTEM

CONTROL: Who Enters and When **RECORD:** Each Event **RECEIVE:** Event Alerts in Real Time

SMART PHONE APP

- 🕷 Open
- M Hold Open
- M Close



ADDITIONAL DESIGN OPTIONS

- Integrates With UNIFY HDC-U330 Cellular HD Camera
- Integrates With UNIFY CTE-U310
- A/C or Solar
- 🗯 Exit Keypad
- Wireless Keypad
- Cellular Booster
- Directional Antenna



CELLULAR WIEGAND ENTRY SYSTEM-CWE

- Open your gate with your cell phone, from anywhere
- Create restricted/unrestricted gate access codes as needed via web
- Receive gate activity alerts via text or email
- Create 'gate hold open' schedules up to one year in advance
- Manage system on secure cloud-based account portal



ALL-INCLUSIVE CELLULAR SYSTEM

- Wiegand Keypad
- Installer and End User Support
- Includes SIM Card and Cellular Service
- # A/C Transformer/Power Supply/Surge Protector (with A/C)
- Solar Panel /Controller (with Solar)

WIEGAND ACCESS CONTROL OPTIONS

- M Card Readers
- **M** Remotes
- M RFID



UNIFY CWE-U320

BY)∭ cellgate

WEB-BASED AUTOMATED CONTROL CENTER



LOUD-BASED BUILT ON MICROSOFT AZURE™

ADMINISTRATION

- Add, change or delete access codes
- Restrict codes to date range, time of day or one-time use
- Schedule opens & closes a year in advance
- Establish login privileges for other users
- Manage receipt of notification alerts: via SMS or email

VIEW HISTORY AND REPORTS

- Events stored for six months
- Identifies: date/time/name of person/ access code
- Sort events by date/time/access code
- Download reports to Excel

Cellgate's Unify Series is a group of access control products designed to work individually or to be intregrated as needed.

INI

CELLGATE'S UNIFY SERIES

CELLULAR WIEGAND ENTRY-CWE

CELLULAR TELEPHONE ENTRY-CTE

CELLULAR HD CAMERA--HDC

STAND ALONE...WORK TOGETHER



ACCESS CONTROL SYSTEM TECHNICAL SPECS

- Up to 4 Wiegand devices per system
- 4 configurable (NO/NC) relays
- 4 digital inputs for monitoring and triggering relays or cameras
- 750 locally stored access codes
- 65,000 access codes total (4 digit codes recommended)
- Post mount keypad
- NEMA 3 steel electronics enclosure: 15"x12"x6"
- Operating temperature: -22 to 167F
- Power (12v DC) Solar: 20 watt solar panel and charge controller (35 AHr battery recommended, not included) AC Power: 3 Amp transformer/power supply with battery charge and automatic failover (battery not included)
- Current draw Complete system:180mA Each additional keypad (including expansion board): 100mA
- Notifications
 Solar: low voltage SMS message
 AC: loss of AC power via SMS message (battery required)
- One-year warranty

) (cellgate