

2MP HDCVI PTZ Camera

32x Starlight IR WDR



HDCVI

- 1/2.8-in. 2MP STARVIS™ CMOS Sensor
- Powerful 32x Optical Zoom
- Supports Multiple Video Formats: HDCVI, CVBS, AHD and TVI
- Starlight Technology for Ultra-low Light Sensitivity
- 1080p at 30 fps or 720p at 30/60 fps, Maximum Resolution
- True Wide Dynamic Range (120 dB), 3D DNR
- Maximum IR Distance up to 150 m (492.13 ft)
- Predictive Focus Analysis (PFA) Technology
- ArcticPro Series Camera - Operational down to -40°C (-40°F)
- IP66 Ingress Protection
- Five-year Warranty*



System Overview

The 2MP Starlight IR PTZ Dome camera features a 1/2.8-in. STARVIS™ CMOS imager with a 32x optical zoom lens, and provides an all in one solution for capturing long-distance video security for outdoor applications, day or night. The camera offers a built-in heater and IP66 Ingress Protection to extend its use to the harshest environments. The PTZ camera is equipped with quick and accurate pan/tilt/zoom control and True WDR for applications with direct sunlight or glare.

Functions

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers light sensitivity that captures details in low light down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Multi-Format Output Support

The camera supports multiple video formats including, HDCVI, CVBS, AHD, and TVI. The camera can switch between these four formats via the OSD menu making the camera compatible with not only HDCVI DVRs but also most existing HD/SD DVRs.

Simplicity

HDCVI technology seamlessly integrates traditional analog security systems with upgraded, high-quality HD video, making it the best choice to protect security investments. The plug and play approach enables full HD video security without the hassles of configuring a network.

Dual Video Output Signals

The camera offers one (1) BNC video output connection to transmit either an HDCVI or a CVBS signal. These output signals allow the camera to integrate with various devices, including analog matrix systems and monitors.

True Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

ArcticPro

The Dahua ArcticPro Series of extreme-environment cameras combine temperature-tolerant components, a waterproof enclosure, and an integrated heater to ensure flawless operation in temperatures as low as -40°C (-40°F). For applications that demand high-resolution video with advanced features in extremely cold environments, the Dahua ArcticPro Series offers a camera to satisfy the most demanding requirements.

Environmental

With a built-in heater and a temperature range of -40°C to $+60^{\circ}\text{C}$ (-40°F to $+140^{\circ}\text{F}$), the camera is designed for extreme temperature environments. Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

Protection

This camera suits even the harsh conditions for outdoor applications. Its 6KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification

Camera

Image Sensor	1/2.8 in. STARVIS™ CMOS
Effective Pixels	1920(H) x 1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	1/3 s to 1/100,000 s
Minimum Illumination	Color: 0.005 lux at F1.6 B/W: 0.0005 lux at F1.6 0 lux at F1.6 with IR on
IR Distance	Distance up to 150.0 m (492.13 ft)
IR On/Off Control	Auto, Manual, Timer
IR LEDs	Four (4)

Lens

Focal Length	4.5 mm to 144 mm
Max. Aperture	F1.6 to F4.0
Angle of View	Horizontal: 2.75° to 60.14° Vertical: 1.54° to 34.41° Diagonal: 3.16° to 68.23°
Optical Zoom	32x
Focus Control	Auto, Semi-automatic, Manual
Close Focus Distance	100 mm to 1500 mm (3.93 in. to 59.06 in.)

DORI Distance¹

Detect (8 ppf)	Observe (19 ppf)	Recognize (38 ppf)	Identify (76 ppf)
1986 m (6515.75 ft)	785 m (2575.46 ft)	398 m (1305.77 ft)	198 m (649.61 ft)

PTZ

Pan/Tilt Range	Pan: 0° to 360° endless; Tilt: -15° to 90° Auto flip 180°
Manual Control Speed	Pan: 0.1° to 300° /s; Tilt: 0.1° to 200° /s
Preset Speed	Pan: 400° /s Tilt: 300° /s
Presets	300
PTZ Mode	5 Pattern, 8 Tour, Auto Pan, Auto Scan
Speed Setup	Human-oriented Focal Length / Speed Adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset, Scan, Tour, Pattern if there is no command in the specified period
Protocol	DH-SD, Pelco-P/D (Auto recognition)

Video

Resolution	1080p (1920 x 1080), 720p (1280 x 720), D1 (704 x 580)	
Frame Rate	1080p at 30 fps or 720p at 30/60 fps	
Video Output	One (1) Channel, BNC High-definition Video Output (HDCVI, AHD, TVI) or CVBS Standard Definition Video Output (switchable)	
Transmission Distance ²	RG-59/U Coax	720p: 500 m (1640.42 ft) 1080p: 400 m (1312.34 ft)
	RG-6/U Coax	720p: 800 m (2624.67 ft) 1080p: 600 m (1968.50 ft)
	CAT 6 UTP (balun required)	720p: 380 m (1246.72 ft) 1080p: 380 m (1246.72 ft)
Day/Night	Auto (ICR), Color, B/W, Timer	
OSD Menu	English, French, German, Italian, Japanese, Polish, Portuguese, Russian, Spanish	
Backlight Compensation	BLC, HLC, WDR (120 dB)	
White Balance	Auto, Indoor, Outdoor, Tracking, Manual, Sodium Lamp, Natural Light, Street Lamp	
Gain Control	Auto, Manual, Iris Priority, Shutter Priority	
Noise Reduction	2D/3D	
Advanced Features	Defog	
Digital Zoom	16x	
Flip	0° / 180°	
Privacy Masking	Up to 24 areas	

Certifications

CE	EN55032, EN55024, EN50130-4
Safety	UL60950-1+CAN/CSA C22.2.No.60950-1
Electromagnetic Compatibility (EMC)	FCC Part 15 subpart B ANSI C63.4- 2014

Interface

Video	Output: One (1) BNC
Audio	Input: One (1) Channel
RS485	One (1) Port (baud rate range: 1200 bps–9600 bps)
Alarm	Input: Two (2) Channels Output: One (1) Channel

Electrical

Power Supply	24 VDC, 2.5 A ±25%
Power Consumption	9.6 W, 22 W with IR on

Environmental

Operating Conditions	-40 °C to 60 °C (-40 °F to +140 °F), Less than 90% RH
Ingress Protection	IP66
Surge Protection	TVS 6000V

Construction

Casing	Metal
Dimensions	∅186.0 mm x 309.0 mm (∅7.32 in. x 12.17 in.)
Net Weight	3.50 kg (7.72 lb)
Gross Weight	6.80 kg (14.99 lb)

1. The DORI distance is a measure of the general proximity for a specific classification to help pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4, the standard that defines the criteria for the Detect, Observe, Recognize and Identify classifications.

2. Transmission distance results verified by real-scene testing in Dahua's test laboratory. Actual transmission distances may vary due to external influences, cable quality, and wiring structures.

Ordering Information

Type	Part Number	Description
2MP PTZ Camera	59232ICLA	2MP 32x Starlight IR PTZ HDCVI Camera, True WDR
Accessories, included	DC24V/2.5 A	Power Supply
	PFA110	Mount Adapter
	PFB300S	Wall Mount
Accessories, optional	PFA120	Junction Box
	PFA140	Power Supply Box
	PFA150	Pole Mount
	PFA151	Corner Mount
	PFB300C	Ceiling Mount
	PFB303S	Parapet Mount

Accessories

Included:



PFB300S
Wall Mount



PFA110
Mount Adapter



DC24V/2.5 A
Power Supply

Optional:



PFA140
Power Box



PFB300C
Ceiling Mount



PFA120
Junction Box



PFA150
Pole Mount



PFA151
Corner Mount



PFB303S
Parapet Mount

Ceiling Mount	Junction Mount
PFA110 + PFB300C	PFA110 + PFB300S + PFA120
Power Box Mount	Pole Mount
PFA110 + PFB300S + PFA140	PFA110 + PFB300S + PFA150
Corner Mount	Parapet Mount
PFA110 + PFB300S + PFA151	PFA110 + PFB303S

Dimensions (mm)

