

Micro SD (TF) Cards

For Use with Dahua Cameras



- 3D TLC NAND Flash Memory
- Supports Class 10 and UHS-I
- Ideal for High-Definition Video Recording
- Water-proof, Shock-Proof, X-ray Proof
- Wide Operating Temperature Range
- Compatible with More Products than Traditional Micro SD Cards
- Fine-tuned for Dahua Products Offering Improved Performance

Technical Specifications ¹			
	DH-PFM112	DH-PFM113	DH-PFM114
Capacity	64 GB	128 GB	256 GB
File System	exFAT		
Format	Micro SDXC		
Speed Class	Class 10, U3		
Bus Mode	High-Speed, UHS-I		
Maximum Read Speed	90 MB/s	90 MB/s	100 MB/s
Maximum Write Speed	20 MB/s	20 MB/s	80 MB/s
Compatibility	Micro SDHC, Micro SDXC, Micro SDHC UHS-I and Micro SDXC UHS-I, Dahua IP Cameras, Thermal Cameras, Network PTZ Cameras, Video Intercom Devices		
Product Dimensions (H x W x D)	100.0 mm x 130.0 mm x 1.0 mm (0.59 in. x 0.43 in. x 0.04 in.)		
Packaging Dimensions (H x W)	15.0 mm x 11.0 mm (3.94 in. x 5.12 in.		
Weight (with package)	8.0 g (0.02 lb)		
Operating Temperature	0° C to 70° C (32° F to 158° F)		
Storage Temperature	−25° C to 85° C (−13° F to 185° F)		
Humidity	0% to 95% (non-condensing)		
Certifications	EN55032, EN55035 ANSI C63.4, CFR 47 FCC PART 15 Subpart B		

^{1.} Performance was tested using a specific testing environment. Different computer systems, operating systems, hardware, software, or functions may influence individual results.