

Universal HD over Coax[®] Digital Video Recorder DW-VA1G416xT

COMPLIANT PRODUCTS					UNIVERSAL	Dimensions				
	W-CIGLIGI			100 MT 700		Unit:	Inch (m	ım)		10.55" (268mm)
	16 сн 480 fps			4K	5 YEAR	ď		1.77″ (45 mm)	14.96" (380mm)	
Unviersal HD over Coax®	16 Channels 480 Total fps	Up to 4K Recording	PathFinder™	Ultra HD Output	Limited Warranty	Spe	ecificat	ions		
Summ	narv					VIDEO Operating s		Embedded Linux®		
							Channel	16 channels		

Summary

 $\mathsf{VMAX}^{\scriptscriptstyle \otimes}$ A1 $\mathsf{G4}^{\scriptscriptstyle \mathsf{IM}}$ is an embedded DVR that records standard analog, HD-Analog and HD-TVI formats at up to 4K resolution and 4K local video output. The DVR is a seamless upgrade to HD resolution for new ROI from existing coaxial infrastructure. Up the Coax (UTC) remote configuration is available with all compatible cameras. The 16-channel VMAX A1 G4 model is NDAA and TAA compliant, and is available with up to 32TB of storage.

Features

- Universal HD over Coax® DVR records HD-Analog, HD-TVI and standard coax up to 4K resolution
- Advanced H.265, H.264 Linux® embedded DVR
- 16-channels, 480fps real-time 30fps recording .
- Up to 4K recording resolution at 112fps (7fps per channel)
- myDW[®] Cloud Management Services
- PathFinder[™] Peer-to-Peer (P2P) remote connection
- Remote management with C3[™] CMS
- · Event camera group recording
- Complete system analysis with real-time system and network status monitoring
- Mobile Application for iOS[®] and Android[®] devices and Apple TV[®]
- OSD and PTZ control via coax (UTC)
- Signal hybrid detects the camera signal automatically
- Instant channel swap, no need to disconnect or reboot the DVR
- Snapshot Notify[™]: programmable interval snapshot email notifications
- 4K (3840 x 2160) True HD, VGA and Spot video outputs
- Up to 32TB internal storage
- HDD calculation and auto-recording configuration
- Thumbnail search with hour and 5-minute previews
- 10-second jump buttons for playback and fast forward
- Event notifications via email, C3 CMS and push notifications
- Compatible with DW[®] Spot[™] Monitoring module for Public Views
- 8 audio inputs, 1 audio output
- 16 sensor inputs, 4 relay outputs
- Simple and free DDNS service
- · Easy web-based client with multi-user access
- Help menu on major functions
- Auto and manual firmware upgrades
- NDAA/TAA compliant
- 5 year limited warranty



C. under and	Channel	16 channels					
System	Signals Supported	Standard analog signal up to 960H, HD-Analog and HD-TVI up to 4K					
	Monitor	True HD, VGA and Spot outputs					
	Frame rate	480fps					
Video out	Resolution	True HD: 3840×2160 (4K), 2560x1440, 1920x1080, 1280x1024, 1024x768, 800x600 VGA: 1920x1080, 1280x1024, 1024x768, 800x600 Spot (CVBS): D1 (720x480)					
	Screen mode	1, 4, 6, 9, 10 and 16					
A 11	Input/output	8 inputs/1 output					
Audio	Codec	ADPCM					
Alarm input	t/output	16 inputs/4 outputs					
Serial		1x RS485					
User interfa	ce	Graphical user interface (GUI), USB mouse					
PERFORM/	ANCE						
	Compression	H.265, H.264					
	Recording mode	Continuous, schedules, sensor-activated, motion detection, pre and post alarm, emergency, quick backup					
	-	Dual recording for live and playback					
Recording	Recording resolutions	3840x2160, 2560x1944, 2560x1440, 1920x1536, 1920x1080, 1280x720 720x480, 960x480					
		D1-Full HD (1920x1080, 1280x720, 720x480, 960x480): 480fps (30fp per channel)					
	Recording and	3MP (1920x1536): 288fps (18fps per channel)					
	playback rate	4MP/2K (2560x1440): 240fps (15fps per channel)					
		5MP (2560x1944): 192fps (12fps per channel)					
		4K (3840x2160): 112fps (7fps per channel)					
Playback	Playback speed Playback functions	x1, x2, x4, x8, x16, x32 Intelli-search by time bar, calendar (date and time), event search and					
	-	thumbnail search					
Storage	HDD interface Maximum internal	2x SATA HDD, 1x e-SATA Up to 32TB internal storage					
	storage HDD health check	Deal time terms alart CMA DT with amail patifications					
	Camera OSD control	Real-time temp alert, S.M.A.R.T. with email notifications Via UTC					
	Digital zoom	Live and playhook					
Features	Software upgrade	Live and playback					
	Mobile client	USB flash drive, network upgrade, FTP remote upgrade Mobile app for Apple and Android devices					
	Covert channel	Yes					
Transaction	verification	Text-in based (USB to serial support, TCP/IP network), display POS data on live and playback					
NETWORK							
LAN		1,000Mbps (RJ45)					
Protocol		Fixed IP, DHCP, UPnP, DDNS					
	Web viewer	Live, playback and configuration up to 10 multiple connections					
	Video streaming	Dual stream for local recording and network transmission					
Access	functions	PathFinder P2P service					
	Client monitoring software	C3 CMS, DW Mobile Plus mobile app and myDW web portal					
Network fu	nctions	Live monitoring, remote playback and file backup					
Remote sys	tem control	Remote system reboot, system management and PTZ control					
NETWORK							
	Firmware upgrade	FTP, USB and CMS over network					
Other function	Special features	Snapshot Notify: Programmable interval camera image verification Event notifications via email, text and C3 CMS Push notifications to mobile devices via DW Mobile Plus Time synchronization to an NTP server (pool.ntp.org)					
	Health check	Real-time system and network status monitoring					
Backup dev		Local backup by USB, network backup by CMS, watermark, AVI file					
		Auto Debast and journaling file a start					

System recovery after power failure Auto-Reboot and journaling file system

DC12V

48W, 4A

5 year limited

CE , FCC, KC, NDAA, TAA

14.96" x 10.58" x 1.77" (380 x 268.8 x 45 mm)

Operating temperature/humidity 32-113 °F (0-45 °C) / 10-90% RH

GENERAL

Certification

Warranty

Power requirements

Power consumption

Dimension (W x D x H)

		®



Available Models

DW-VA1G416 - 16CH, no HDD. DW-VA1G4162T - 16CH, 2TB internal storage. DW-VA1G4164T - 16CH, 4TB internal storage. DW-VA1G4166T - 16CH, 6TB internal storage. DW-VA1G41610T - 16CH, 8TB internal storage. DW-VA1G41610T - 16CH, 10TB internal storage. DW-VA1G41612T - 16CH, 12TB internal storage. DW-VA1G41616T - 16CH, 16TB internal storage. DW-VA1G41616T - 16CH, 20TB internal storage. DW-VA1G41620T - 16CH, 20TB internal storage.

Accessories (optional)



DW-G419RE 19" rack mount ears



