













Summary

This MEGApix® IP camera provides 1080p, 2.1 megapixel resolution at realtime 30fps. It includes a 4mm fixed lens with image enhancement features such as 120db True WDR, Samrt IR™ and Smart DNR™, all in an IP66, IK10-rated vandal-resistant housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP 1/2.7" Image Sensor at Real-time 30fps
- · 4mm Fixed Lens
- True Wide Dynamic Range (WDR)
- Dual Codecs (H.264, MJPEG) with Simultaneous Streaming
- 50' Smart IR™ with Intelligent Camera Sync
- Smart DNR™ 3D Digital Noise Reduction
- · True Day/Night Mechanical IR Cut Filter
- · Programmable Privacy Zones
- · Auto Gain Control (AGC)
- Backlight Compensation (BLC)
- · Auto White Balance (AWB)
- · Motion Detection
- · Micro SD/SDHC/SDXC Class 10 Card Slot for Event and Continuous Recording(Card Not Included)
- · Web Server Built-in
- · PoE Class 2 / DC12V
- · ONVIF Conformant, Profile S
- · IP66 Certified Weather and Tampering Resistant
- IK10-Rated Impact-Resistant
- 5 Year Warranty

Accessories (Optional)



DWC-V7WM Wall Mount for V7 Outdoor Dome Cameras




DWC-V7JUNC Junction Box for V7 Outdoor Dome Cameras




DWC-V7CM Ceiling Mount for V7 Outdoor Dome Cameras

Dimensions

unit: Inch (mm)





4.1" (105mm)

Specifications

IMAGE	2.1MP 1/2.7"MP CMOS
Image Sensor Effective Pixels	
Effective Pixels	1928(H) x 1088(V)
Minimum Scene Illumination	F2.6 (30IRE): 0.39 Lux (Color) F2.6 (30IRE): 0.0 Lux (B&W)
LENS	
Focal Length	4.0mm, F2.0
Lens Type	Fixed Lens
IR Distance	50ft Range IR
Angle of View	88°
OPERATIONAL	
Shutter Mode	Auto, Manual, Anti-Flickering
Shutter Speed	1/15~1/32000
Slow Shutter	Off, 2x, 3x, 5x, 6x, 7.5x, 10x
Smart DNR™ 3D Digital Noise Reduction	0~11
Auto Gain Control	Auto
Wide Dynamic Range (WDR)	Off, 2x
Wide Dynanmic Range dB	120dB
Day and Night	Auto, Day (Color), Night (B/W)
Privacy Zones	16 Programmable Privacy Zones
Alarm Notifications	Notifications Via E-mail, SD Card or FTP Server
Memory Slot	Micro SD / SDHC / SDXC. Card not Included
NETWORK	WILCIO 3D / 3DHC / 3DXC. Card Hot Hichaded
LAN	200 2 Campliance 10/100 LAN
	802.3 Compliance 10/100 LAN
Video Compression Type	H.264, MJPEG
Resolution	1920x1080 ~ 480p(30fps)
Frame Rate	Up to 30fps at All Resolutions
Video Bitrate	100kbps~10Mbps, Multi-rate for Preview and Recording
Bitrate Control	Multi Streaming CBR/VBR at H.264 (Controllable frame rate Bandwidth)
Streaming Capability	Dual-Stream at Different Rates and Resolutions
IP	IPv4
Protocol	ONVIF, TCP/IP, UDP, RTP(UDP/TCP), RTSP, NTP, HTTP,HTT SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2c/ v3(MIB-2)
Security	Password authentication, Multi-level user configuration HTTPS(SSL), IP filtering, 802.1x, Digest Authentication(ID/
Maximum User Access	10 Users
ONVIF Conformance	Yes
W 1 12	OS: Windows®, MAC® OS, Linux®
Web Viewer	Browser: Internet Explorer, Chrome, Firefox, Safari
Video Management Software	DW Spectrum® IPVMS
ENVIRONMENTAL	·
Operating Temperature	-4°F~122°F (-20°C~50°C)
Operating Humidity	Less than 90% (Non-Condensing)
IP Rating	IP66 Certified Weather and Tampering Resistant
IK Rating	IK10 Impact Resistant
Other Certifications	CE, FCC, RoHS
ELECTRICAL	02,100,1010
Power Requirement	(Adaptor not included) DC 12V, POE IEEE 802.3af Class2
r owor nequirement	
Power Consumption	PoE: Max. 5.4W DC 12V: 3.8W
MECHANICAL	
THE OTH THE OTHER	
Material	Aluminum Die-casting
	Aluminum Die-casting 4.13 x 2.38 in (105 x 60.7mm)



