













5YEAR

Summary

This MEGApix® IP camera provides 1080p, 2.1 megapixel resolution at real-time 30fps. It includes a 6mm fixed lens with image enhancement features such as 120db True WDR, Samrt IR™ and Smart DNR™, all in an IP66, IK10-rated vandal-resistant housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP 1/2.7" Image Sensor at Real-time 30fps
- · 6mm Fixed Lens
- True Wide Dynamic Range (WDR)
- Dual Codecs (H.264, MJPEG) with Simultaneous Streaming
- 50' Smart IR™ with Intelligent Camera Sync
- Smart DNR™ 3D Digital Noise Reduction
- · True Day/Night Mechanical IR Cut Filter
- · Programmable Privacy Zones
- Auto Gain Control (AGC)
- Backlight Compensation (BLC)
- Auto White Balance (AWB)
- · Motion Detection
- Micro SD/SDHC/SDXC Class 10 Card Slot for Event and Continuous Recording(Card Not Included)
- · Web Server Built-in
- · PoE Class 2 / DC12V
- ONVIF Conformant, Profile S
- IP66 Certified Weather and Tampering Resistant
- IK10-Rated Impact-Resistant
- 5 Year Warranty

Accessories (Optional)



DWC-V7WM Wall Mount for V7 Outdoor Dome Cameras




DWC-V7JUNC Junction Box for V7 Outdoor Dome Cameras




DWC-V7CM Ceiling Mount for V7 Outdoor Dome Cameras

Dimensions

unit: Inch (mm)





4.1" (105mm)

Specifications

IMAGE Image Sensor	2.1MP 1/2.7" CMOS
Effective Pixels	1928(H) x 1088(V)
	F2.0 (30IRE): 0.25 Lux (Color)
Minimum Scene Illumination	F2.0 (30IRE): 0.0 Lux (B&W)
LENS	
Focal Length	6.0mm, F2.0
Lens Type	Fixed Lens
IR Distance	50ft Range IR
Angle of View	54°
OPERATIONAL	
Shutter Mode	Auto, Manual, Anti-Flickering
Shutter Speed	1/15~1/32000
Slow Shutter	Off, 2x, 3x, 5x, 6x, 7.5x, 10x
Smart DNR™ 3D Digital Noise Reduction	0~11
Auto Gain Control	Auto
Wide Dynamic Range (WDR)	Off, 2x
Wide Dynanmic Range dB	120dB
Day and Night	Auto, Day (Color), Night (B/W)
Privacy Zones	16 Programmable Privacy Zones
Alarm Notifications	Notifications Via E-mail, SD Card or FTP Server
Memory Slot	Micro SD / SDHC / SDXC. Card not Included
NETWORK	
LAN	802.3 Compliance 10/100 LAN
Video Compression Type	H.264, MJPEG
Resolution	1920x1080 ~ 480p(30fps)
Frame Rate	Up to 30fps at All Resolutions
Video Bitrate	100kbps~10Mbps, Multi-rate for Preview and Recording
VIUEO DILIALE	Multi Streaming CBR/VBR at H.264 (Controllable frame rate
Bitrate Control	Bandwidth)
Streaming Capability	Dual-Stream at Different Rates and Resolutions
IP	IPv4
Protocol	ONVIF, TCP/IP, UDP, RTP(UDP/TCP), RTSP, NTP, HTTP,HTTI SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2c/ v3(MIB-2)
Security	Password authentication, Multi-level user configuration HTTPS(SSL), IP filtering, 802.1x, Digest Authentication(ID/I
Maximum User Access	10 Users
ONVIF Conformance	Yes
Web Viewer	OS: Windows®, MAC® OS, Linux® Browser: Internet Explorer, Chrome, Firefox, Safari
Video Management Software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating Temperature	-4°F~122°F (-20°C~50°C)
Operating Humidity	Less than 90% (Non-Condensing)
	IP66 Certified Weather and Tampering Resistant
IP Rating	II OO GELIIIEU WEALIEL AND TAINDENING NESISTAIL
IF Rating IK Rating	IK10 Impact Resistant
<u> </u>	
IK Rating	IK10 Impact Resistant
IK Rating Other Certifications ELECTRICAL	IK10 Impact Resistant CE, FCC, RoHS
IK Rating Other Certifications	IK10 Impact Resistant CE, FCC, RoHS (Adaptor not included) DC 12V, POE IEEE 802.3af Class2 PoE: Max. 5.4W
IK Rating Other Certifications ELECTRICAL Power Requirement Power Consumption	IK10 Impact Resistant CE, FCC, RoHS (Adaptor not included) DC 12V, POE IEEE 802.3af Class2
IK Rating Other Certifications ELECTRICAL Power Requirement Power Consumption MECHANICAL	IK10 Impact Resistant CE, FCC, RoHS (Adaptor not included) DC 12V, POE IEEE 802.3af Class2 POE: Max. 5.4W DC 12V: 3.8W
IK Rating Other Certifications ELECTRICAL Power Requirement	IK10 Impact Resistant CE, FCC, RoHS (Adaptor not included) DC 12V, POE IEEE 802.3af Class2 PoE: Max. 5.4W







