



# Summary

This MEGApix® IP camera provides 4 megapixel resolution at real-time 30fps. It includes a 4mm fixed lens with image enhancement features such as 120db True WDR, Smart IR™ and Smart DNR™, all in an IP66, IK10-rated vandal resistant housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

#### **Features**

- 4MP 1/3" CMOS Sensor at Real-Time 30fps
- 4mm Fixed Lens
- True Wide Dynamic Range (WDR)
- · Dual Codecs (H.264, MJPEG) with Simultaneous Streaming
- 50' Smart IR™ with Intelligent Camera Sync
- Smart DNR™ 3D Digital Noise Reduction
- · True Day/Night with Mechanical IR Cut Filter
- · Programmable Privacy Zones
- Dynamic Range Compression (DRC)
- Auto Gain Control (AGC)
- Backlight Compensation (BLC)
- Auto White Balance (AWB)
- · Motion Detection
- Micro SD/SDHC/SDXC Class 10 Card Slot for Event and Continuous Recording (Card Not Included)
- Web Server Built-in
- PoE Class 3 / DC12V
- ONVIF Conformant, Profile S
- · IP66 Weather and Tampering Resistant
- IK10-Rated Impact-Resistant
- 5 Year Warranty

### Accessories (Optional)



DWC-V7WM Wall Mount for V7 Outdoor Dome Cameras




DWC-V7JUNC Junction Box for V7 Outdoor Dome Cameras




DWC-V7CM Ceiling Mount for V7 Outdoor Dome Cameras

## **Dimensions**

unit: Inch (mm)





4.1" (105mm)

### Specifications

| IMAGE<br>Image Sensor                 | 4MP 1/3" CMOS   |
|---------------------------------------|---|
| Effective Pixels                      |   |
| Effective Pixels                      | 2688(H) X 1520(V)   |
| Minimum Scene Illumination            | F2.0 (30IRE): 0.41 Lux (Color)<br>F2.0 (30IRE): 0.0 Lux (B&W)   |
| LENS                                  |   |
| Focal Length                          | 4.0mmm, F2.0  |
| Lens Type                             | Fixed Lens  |
| IR Distance                           | 50ft Range IR   |
| Angle of View                         | 81°   |
| OPERATIONAL                           |   |
| Shutter Mode                          | Auto, Manual, Anti-Flickering   |
| Shutter Speed                         | 1/15~1/32000  |
| Slow Shutter                          | Off, 2x, 3x, 5x, 6x, 7.5x, 10x  |
| Smart DNR™ 3D Digital Noise Reduction | 0~11  |
| Auto Gain Control                     | Auto  |
| Wide Dynamic Range (WDR)              | Off, 2x, 3x   |
| Wide Dynanmic Range dB                | 120dB   |
| Day and Night                         | Auto, Day (Color), Night (B/W)  |
| Privacy Zones                         | 16 Programmable Privacy Zones   |
| Alarm Notifications                   | Notifications Via E-mail, SD Card or FTP Server   |
| Memory Slot                           | Micro SD / SDHC / SDXC. Card not Included   |
| NETWORK                               | MICTO 3D / 3DRC / 3DAG. Card flot included  |
|                                       | 000 2 Compliance 10/100 LAN   |
| LAN<br>Video Compression Tune         | 802.3 Compliance 10/100 LAN   |
| Video Compression Type                | H.264, MJPEG  |
| Resolution                            | 1440p ~ 480p (30fps)  |
| Frame Rate                            | Up to 30fps at All Resolutions  |
| Video Bitrate                         | 100kbps~10Mbps, Multi-rate for Preview and Recording  |
| Bitrate Control                       | Multi Streaming CBR/VBR at H.264 (Controllable frame rate<br>Bandwidth)   |
| Streaming Capability                  | Dual-Stream at Different Rates and Resolutions  |
| IP                                    | IPv4  |
| Protocol                              | ONVIF, TCP/IP, UDP, RTP(UDP/TCP), RTSP, NTP, HTTP,HTTI<br>SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2c/<br>v3(MIB-2) |
| Security                              | Password authentication, Multi-level user configuration HTTPS(SSL), IP filtering, 802.1x, Digest Authentication(ID/I      |
| Maximum User Access                   | 10 Users  |
| ONVIF Conformance                     | Yes   |
| Web Viewer                            | OS: Windows®, MAC® OS, Linux®   |
|                                       | Browser: Internet Explorer, Chrome, Firefox, Safari   |
| Video Management Software             | DW Spectrum® IPVMS  |
| ENVIRONMENTAL                         |   |
| Operating Temperature                 | -4°F~122°F (-20°C~50°C)   |
| Operating Humidity                    | Less than 90% (Non-Condensing)  |
| IP Rating                             | IP66 Certified Weather and Tampering Resistant  |
| IK Rating                             | IK10 Impact Resistant   |
| Other Certifications                  | CE, FCC, RoHS   |
| ELECTRICAL                            | 52,1 55,1316  |
| Power Requirement                     | (Adapor not included) DC 12V, POE IEEE 802.3af Class3   |
| i owor rioquitement                   |   |
| Power Consumption                     | PoE: Max 7.4W<br>DC 12V: Max 5.6W   |
| MECHANICAL                            |   |
| MEGNANICAL                            |   |
| MECHANICAL<br>Material                | Aluminum Die-casting  |
|                                       | Aluminum Die-casting<br>4.13 x 2.38 in (105 x 60.7mm)   |







