



































4K Output HD IPC

DDNS

Network

Audio

CMS

Mouse

STD

MIC

Mobile


USB

E-mail

VCA

ED9308H5NV-8P-A series are 8 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition PoE NVRs, which adopt the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

ED9308H5NV-8P-A series integrate with 8 PoE network ports and support 8 CH IPC direct connection to NVR, simultaneous 8 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



ED9308H5NV-8P-A

SPECIFICATIONS

Model		ED9308H5NV-8P-A
Compression		Standard H.265/H.264
System	OS	Embedded Linux
Video	Network Input	8CH IPC input
	Network	·
	Bandwidth	80Mbps/80Mbps (access/transfer)
	Network Access Format	8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps
	Output	HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768
Audio	Network Input	8 CH IPC audio input
	2-way Audio	RCA×1
	Local Output	RCA×1
Record	Record Stream	Dual stream recording
	Resolution	8MP/5MP/4MP/3MP/1080P/960P/720P
	Mode	Manual, timer, motion, sensor
Playback	Simultaneous Playback	Max 8 CH
	Search	Time slice / time / event / tag search
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	Mode	Manual, sensor, motion, exception
	Input	8 CH local alarm input, support 8CH IPC alarm input
	Output	4 CH
	Triggering	Record, snap, preset, e-mail, etc.
Face	Channel	8 CH
	Face Picture Database	16 libraries 10000 Face Pictures
	Computing Capability	240 pictures / minute
	Face Picture Search	Search by picture is supported
	Database Management	Add, modify, delete and search face pictures
	Face Picture Adding	Add face pictures through APP, WEB and local PC
	External face	Resolution: 64 x 64 ~ 1920 x 1080
	picture enrollment	Size∶lessthan 200KB Format∶jpg
	Face Picture Comparison	Support allow list and block list alarm
	Face Trace	Yes
	Map of Face Trace	Reolution: $600 \times 300 \sim 3840 \times 2160$ Size: within 200KB Format: jpg
	Statistic Graph of Face Information	Bar graph, pie chart
	Statistic Mode of Face Information	Statistics by day, week, month, quarter as well as customized time period
Network	Interface	RJ 45 1000 Mbps × 1
	PoE Port	RJ 45 × 8
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
L	Web Client	Multiple users online
Mobile Device	os	iOS, Andriod
Storage	HDD	SATA × 1, max 8T

Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	RS 485	RS485 × 2, connect to PTZ or keyboard
	USB	USB 2.0 \times 1 , USB 3.0 \times 1 (one in the front panel and the other in the rear panel)
	Remote Controller	Optional
Others	Power Supply	DC48V/2.5A
	Consumption	≤ 15W (without HDD)
	Dimensions (mm)	300 × 248 × 52 (W × D × H)
	Work Environment	-10 ~ 50 °C , 10% ~ 90% humidity

Features

- Support 8 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 8 CH simultaneous playback
- Search: time slice, time, event (manual, sensor, motion), tag search
- Support face detection and comparison
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- 8 PoE network ports, support IPC direct connection to NVR; support PoE power supply
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

DIMENSIONS

