

































4K Output HD IPC

DDNS

Network

Audio

MIC

Mobile

CMS

USB

Mouse

E-mail

STD

ED9732H5NV-Aseries are 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition NVRs, which adopt the most advanced

SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system.

ED9732H5NV-Asupport 32 CH IP input, simultaneous 16 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

ED9732H5NV-A

SPECIFICATIONS


Model		ED9732H5NV-A
Cuatam	Compression	Standard H.265
System	os	Embedded Linux
Video	Network Input	32 CH IPC input
	IP Input Access / Transfer Bandwidth	256Mbps / 256Mbps
	Network Access Format	8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps
	Output	HDMI × 2 : one of 4K × 2K / 1920 × 1080 / 1280 × 1024 the other of 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024
Audio	Network Input	32 CH IPC audio input
	2-way Audio	RCA×1
	Local Output	RCA×1
	Record Stream	Dual stream recording
Record	Resolution	8MP/5MP/4MP/3MP/1080P/960P/720P@25/30fps
	Mode	Manual, timer, motion, sensor
	Simultaneous Playback	Max 16 CH
	Search	Time slice / time / event / tag search
Playback	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	Mode	Manual, sensor, motion, exception
	Input	8 CH local alarm input, support IPC alarm input
	Output	4 CH
	Triggering	Record, snap, preset, e-mail, etc.
	Channel	32 CH
	Face Picture	16 libraries
	Database	10000 Face Pictures
	Computing Capability	240 pictures / minute
	Face Picture Search	Search by picture is supported
	Database Management	Add, modify, delete and search face pictures
	Face Picture Adding	Add face pictures through APP, WEB and local PC
Face	External face	Resolution: 64 x 64 ~ 1920 x 1080
	picture enrollment	Size : less than 200KB Format : jpg
	Face Picture Comparison	Support allow list and block list alarm
	Face Trace	Yes
	Map of Face Trace	Reolution: $600 \times 300 \sim 3840 \times 2160$ Size: within 200KB Format: jpg
	Statistic Graph of Face Information	Bar graph, pie chart
	Statistic Mode of Face Information	Statistics by day, week, month, quarter as well as customized time period
	Statistic Mode of Face	
Network	Statistic Mode of Face Information	customized time period
Network	Statistic Mode of Face Information	customized time period RJ45 10 / 100 / 1000 Mbps × 2
Network Mobile Device	Statistic Mode of Face Information Interface	customized time period RJ45 10 / 100 / 1000 Mbps × 2 TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Mobile	Statistic Mode of Face Information Interface Protocol Web Client	customized time period RJ45 10 / 100 / 1000 Mbps × 2 TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP Max 10 users online

Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
Port	USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel), USB 3.0 × 1 (rear panel)
	Remote Controller	Yes
Others	Power Supply	ATX
	Consumption	≤ 15W (without HDD)
	Dimensions (mm)	430 × 453 × 89 (W × D × H) 445 × 436 × 90 (W × D × H)
	Work Environment	-10 ~ 50 °C , 10% ~ 90% humidity

FEATURES

- Support 32 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 16 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Support face detection and comparison
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

DIMENSIONS



ED9732H5NV-A

REAR PANEL

