

## SID-MD

### Video Intercom Display Module




#### Key Feature

- 3.5-inch LCD screen with resolution: 320 × 480p
- 4 physical buttons with backlight
- Up to 2000 contacts can be added to the device
- Stores and searches contact list
- Dials number and calls indoor station with keypad module
- Unlocks door by PIN code with keypad module
- Multiple languages


## Specifications

Model	DS-KD-DIS	
System parameters	Processor	Embedded MCU processor
	Storage	64 MB
	Flash	8 MB
Display parameters	Screen	3.5-inch TFT LCD screen
	Resolution	320 × 480p
	Backlight	Supported
	Operation method	Physical buttons
Interfaces	RS-485	Module-connecting (1 input, 1 output)
	Power input	12 VDC (From the other module)
	Power output	12 VDC (For the other module)
	Physical buttons	4 (Up, Down, OK, Back)
	Debug port	1
General	Power consumption	≤ 3 W
	Working temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Working humidity	10% to 95%
	Protection level	IP65

## Typical Application



## Appearance



No.	Description	No.	Description
1	Screen	5	Back Button
2	Up Button	6	Module-Connecting Interface (Output)
3	Down Button	7	Module-Connecting Interface (Input)
4	Confirm Button	8	Debug Port