



KPROX2 or WSSKP1
 6 CONDUCTOR SHIELDED 22GA
 MAX. DISTANCE 500'

2 X 16.5 VAC, 37 OR 40VA TRANSFORMER (NOT SUPPLIED)

12V DC/7AH BACK UP BATTERY (NOT SUPPLIED)

16 x 2 N/O FLOOR INPUTS

RIBBON CABLE

OPTIONAL EQUIPMENT

ADD OCB8 IN BANKS OF 8 TO CONTROL UP TO 40 FLOORS

ADD UP TO 4 OCB8'S

1 OCB8 BOARD (STANDARD)

SPDT DRY CONTACTS STATIC PROTECTED

A CB485 IS REQUIRED PER CONTROLLER WHEN THERE IS MORE THAN ONE ON SITE

CB485

MULTIPLE PANELS

2 TWISTED PAIRS (CAT5) MAX. DISTANCE 2000'

5 CONDUCTOR SHIELDED 22GA MAX. DISTANCE 100' DIRECT CONNECT RS232

NETCOM2P/6P CB485

MC9600 MODEM

DATA CABLE (40-2322)

LAN/WAN

REMOTE SITE

TELEPHONE LINE OR LAN/WAN TO REMOTE SITES

MODEM (MC33H)

* Combine with KeyScan's family of controllers

OVERVIEW OF THE FEATURES IN EVERY KEYSKAN SYSTEM

		PoE Single Door Control System	Keyscan Multiple Reader Control Systems				Keyscan Elevator Control Systems	
								
		CA150	CA250	CA4500	CA8500	EC1500	EC2500	
Access Control Unit	Doors Supported	1 door	2 doors	4 doors	8 doors	1 cab up to 40 floors	2 cabs / up to 16 floors	
	Reader Ports	2 (In/Out)	2	4	8	1	2	
	Multi -ACU Support	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	
	System Status LEDs	Yes	Yes	Yes	Yes	Yes	Yes	
	Dual Processors	Yes	Yes	Yes	Yes	Yes	Yes	
	Flash Memory	Yes	Yes	Yes	Yes	Yes	Yes	
	Power Fail Output	NA	Yes	Yes	Yes	NA	NA	
	Floor Monitor Inputs (Supervised)	NA	NA	NA	NA	Yes	Yes	
Inputs	Request to Exit (RTE) Inputs (Supervised)	1	2	4	8	NA	NA	
	Door Contact Inputs	1	2	4	8	NA	NA	
	Auxiliary Inputs (Supervised)	2	8	16	16	NA	NA	
	I/O Input Expansion	NA	NA	64 (banks of 16)	64 (banks of 16)	NA	NA	
Outputs	Auxiliary Output Relays	1	2	4	8	NA	NA	
	Expansion Auxiliary Output Relays	NA	NA	8	8	NA	NA	
	I/O Outputs	NA	NA	64 (banks of 16)	64 (banks of 16)	NA	NA	
	Door Output Relays	1	2	4	8	NA	NA	
Capacity	No. of Cardholders	32,000	32,000	32,000	32,000	32,000	32,000	
	Transaction File Buffer	6000	6000	6000	6000	6000	6000	
	Time Zones	256	256	256	256	256	256	
	Time Schedules	512	512	512	512	512	512	
	Group Levels	511	511	511	511	511	511	
	Holiday Dates	64	64	64	64	64	64	
Connectivity	Ethernet Ready	Equipped	Optional	Optional	Optional	Optional	Optional	
	POE - Power over Ethernet (IEEE 802.3af)	Equipped	NA	NA	NA	NA	NA	
	CMAC Reverse IP	Equipped	Optional	Optional	Optional	Optional	Optional	
	Serial Communication	Yes (single panel)	Yes	Yes	Yes	Yes	Yes	
	Dial Up Communication (Optional)	NA	Yes	Yes	Yes	Yes	Yes	

Keyscan's family of Access Control Units are inter-dependable and scalable to support any sized application.

KEYSCAN INC.

901 Burns Street East, Whitby, ON Canada L1N 6A6
 Phone: +1 905.430.7226 Fax: +1 905.430.7275
 Toll Free: +1 888-KEYSCAN (539.7226)
 Web Site: www.keyscaan.ca

Keyscan Inc. reserves the right to alter designs and specifications without notice or obligation