

## Explosion Proof Camera w/ Video Control Box Cart - Optical/Digital Zoom, 1TB NVR, Wireless NC, EXP Wi-Fi Antenna - 200' 12/4 Cord

**EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



### EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 Explosion Proof Camera System

#### Video Control Box Cart Specs

**Listing:** NRTL Listed for United States & Canada

**Cart Dimensions:** -

**Weight:** -

**Power Cart Voltage:** 120V

**NVR Storage Capacity:** 1TB

**Network Card:** Wireless

**Antenna Type:** EXP Wi-Fi

**Materials:** Copper-free Aluminum

**Cart Finish:** Powder Coated Blue

**Mount:** Powder Coated Aluminum Dolly Cart w/ Run Flat Tires

**Disconnect Receptacle:** (1)

**Power Cord:** 10' Cord w/ 20A KP-20ABC Pin/Sleeve, 2W3P Plug

#### EXP Camera Specs

**Watts:** 12W

**Voltage:** 120-240V AC

**Image Sensor:** CMOS

**Signal System:** NTSC

**Connectors:** Terminal Strips

**Effective Pixels:** 1956(H) \* 1266(V)

**Min. Illumination:** 0.1 Lux @ F1.2 AGC On / 0 Lux w/ IR

**Shutter Speed:** 1/25(1/30s) to 1/50,000s

**Lens:** 5-50mm Focal Length

**Angle of View:** 90°

**Day/Night:** ICR

**Video Framerate:** 1080p @ 30fps

**Video Output:** Analog over Copper Wire

**Signal to Ratio:** >62 dB

**Language:** English

#### Light Specs

**Watts:** 12W

**Voltage:** 120-240V AC

**Lumens:** 1,320

**Luminous Efficacy:** 110 Lm/W

**LED Light Color:** 6000K - White

#### Ratings/Approvals:

##### Video Control Box Enclosure Ratings

Class I, Divisions 1 & 2, Groups B\*\*, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Divisions 1 & 2, Groups E, F, G

Class III, Divisions 1 & 2

NEMA 3R, 4, 7, 9

\*\*Conduit seals required within 18" for Group B applications

##### Camera Ratings

Class I, Divisions 1 & 2, Groups B, C, D

Class I, Zones 1 & 2, Groups IIB+H2, IIA

Class II, Divisions 1 & 2, Groups E, F, G

Class III, Divisions 1 & 2

NEMA 3R, 4, 7 (B, C, D), 9 (E, F, G)

NRTL Listed to UL 508A

NRTL Listed to UL 1203

NRTL Listed to CSA C22.2 No 14, 25, 30

**LED Life Expectancy:** 50,000 hours  
**Lighting Configuration:** 10° Spot or 40° Flood  
**Spot Beam:** 800`L x 140`W  
**Flood Beam:** 300`L x 225`W  
**Ambient Operating Temp Range:** -40°C to +60°C  
**Housing Material:** Aluminum  
**Light Housing Color:** Powder Coated - Grey  
**Lens Material:** Polycarbonate  
**Mounting:** Adjustable Surface Mount Brackets w/ Set Screws  
**Cord Configuration:** 200` 12/4 SOOW Cord w/ EXP Plug

**Special Orders - Requirements**

Contact us for special requirements

**Toll Free: 1-800-369-6671**

**Intl: 1-214-616-6180**

**Fax: 1-903-498-3364**

**E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)**

**The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 from Larson Electronics is an Explosion Proof Camera w/ Video Control Box Cart that is designed for security and remote observation in both indoor and outdoor hazardous environments during the day and night. The 1080p HD high resolution security camera features a 150` range, 10x optical zoom with autofocus, and 62x digital zoom for maximum coverage and accuracy. A digital inverter supports both HD-TVI and CVBS analog output. Equipped with an explosion proof light, a powder coated aluminum video control box cart hosts supporting recording devices and network equipment for wireless network connections.**

The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 offers mobile video recording and monitoring in combustible facilities. This system includes an explosion proof camera with LED light that is supported by a video control box cart. The video control box cart contains an explosion proof enclosure protecting a recording device with 1TB of storage, wireless network card and explosion proof Wi-Fi antenna. The unit is capable of generating its own Wi-Fi network. Operators can connect their devices to this network to access the video recorder or for live viewing streams from the camera.

**Camera Features:** The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 security camera provides operators in hazardous areas with crisp 1080p HD high resolution images. A 5-50mm motorized lens automatically adjusts focus, providing operators with a precise 10x optical zoom and autofocus and 62x digital zoom image. A digital inverter supports both HD-TVI and CVBS analog output to a customer provided remote mount DVR system. This camera measures a compact 12.34" x 3.96" x 4.22" and the mounting base allows for precise aiming with 90° of vertical adjustment.



**In-Use Robotic Sandblasting**

The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 security camera is built to perform under harsh and rugged conditions. This IP67 rated waterproof unit resists the corrosive effects of weather, dust, dirt, and humidity. This Class I Divisions 1 & 2, Class II Divisions 1 & 2, Class III Divisions 1 & 2 rated camera provides property and product security while also protecting operators with its safe and reliable explosion proof and weatherproof design.

**Light Features:** The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 produces 1,320 lumens of high-intensity LED light for illumination within hazardous areas and potentially explosive work environments. This explosion proof LED light fixture operates on 120-240V AC. The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 is available in two lighting configurations; spot and flood. The spot configuration features a 10° beam that measures 800`L and 140`W. The flood configuration throws a 40° beam that measures 300`L and 225`W. An adjustable surface mount mechanism allows operators to control the direction

of the beam by tilting the unit towards the desired target.

**LED Benefits:** Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

**Heat Management:** Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED's core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

**Durability:** The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 explosion proof camera & LED light combination fixture from Larson Electronics is rated NEMA Type 3, 4, 4X, 7 (B,C,D) and 9 (E,F,G) and designed to withstand the rigors of demanding environmental and operating conditions while remaining lightweight and easy to use. These units can operate in temperatures of -40° Celsius to 60° Celsius, are waterproof to 3 meter and resist ingress of dust, dirt and humidity. The housings are formed from extruded aluminum and the lenses are unbreakable polycarbonate. The LEDs offer inherent LED resistance to shocks and vibrations.

**Wiring:** This video control box cart system is designed to operate on 120V AC and contains a 10' power cord with a 20-amp KP-ABC pin/sleeve explosion proof plug. The camera is connected to 200' of 12/4 SOOW cord with an explosion proof male plug, which connects to a disconnect receptacle on the video control box cart.

**Camera and LED Light Mounting:** The EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1 explosion proof security camera & LED light combination fixture is secured to flat surfaces, such as a ceiling or wall, using and adjustable reverse pedestal style brackets. The included mounting bracket allows 90° vertical adjustment and 360° of swivel for precision aiming. The camera and the light each have their own bracket for mounting reliability and are connected via piping for increased strength and mounting durability.

**Video Control Box Cart:** A powder coated aluminum cart frame holds the recording device, wireless network card, explosion proof Wi-Fi antenna and power cord, resulting in an extremely stable, durable, and mobile video cart platform. These components (except the power cord) are protected by a heavy-duty explosion proof enclosure. Two, no-flat rubber wheels and a dolly cart style mounting platform provides easier mobility, and the upper handle allows easy lifting with cable or chain hooks.

**Applications:** Vessel, tank and reactor monitoring, remote observation of



external facilities, offshore and land based rigs, indoor and outdoor security, commercial buildings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.

---



---

## Frequently Asked Questions (FAQ)





**Options:**

**EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1-Beam Config**

**Example: EXPCMR-ALG-OZ-IC-1080P-LE1-1227-200C-12.4-WF-M1-SP**

| Beam Config |     |
|-------------|-----|
| SPOT        | -SP |
| FLOOD       | -FL |



Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)