

5G108-BL5

GigaMax Cat 5e QuickPort Jack QuickPack, 25-pack, Blue



UPC Code : 078477203040

Country Of Origin : United States

RoHS Compliant : Yes

The GigaMax Category 5e UTP QuickPort Jack is designed to be used with any Category 5e UTP structured cabling system. The modular connector features a one-piece narrow design that supports high port density in a small area, and is ideal for use in residential, MDU, and high-megabit applications.

Technical Information

Product Features

Body Color : Blue

Brand : GigaMax

Cable Type : 8-Conductor UTP Copper
Cat 5, 5e and 6

Category Rating : Cat 5e

Color : Blue

Connector Feature : Channel-Rated

Contact Base Material : Phosphor
Bronze

Contact Sub-Surface Material : 100
microinches thick Nickel-Plated

Contact Surface Material : 50
microinches thick Gold-Plated

Flammability : Rated V-0 per UL 94

Module Style : Connector

Module Type : Category 5e

Ordering Notes : Bulk Package of 25

Packaging : QuickPack 25/bag

Position / Conductor : 8P8C

Shielding : UTP

Standards and Certifications : TIA/EIA
cULus Listed

Termination Type : 110 Punchdown

Warranty : 1 Year Limited

Material Specifications

Body Color : Blue

Body Material : High-Impact Fire-
Retardant Plastic

Contact Base Material : Phosphor
Bronze

Contact Sub-Surface Material : 100
microinches thick Nickel-Plated

Contact Surface Material : 50
microinches thick Gold-Plated

Mechanical Specifications

Cable Type : 8-Conductor UTP Copper
Cat 5, 5e and 6

Connector Feature : Channel-Rated

Position / Conductor : 8P8C

Product ID : Permanently laser-
engraved

Style Name : GigaMax

Termination Type : 110 Punchdown

Wiring Standard : T568A T568B

Performance Specifications

Module Type : Category 5e

Standards and Certifications

ACA : Compliant

CSA : Certified

FCC : Part 68 Compliant

NEC : Article 800 Compliant

TIA/EIA : TIA-568-B

UL : cULus Listed

Features and Benefits

- Available in 13 colors
- Dual wiring code label allows connector to be wired to either T568A or T568B
- Individual port configurability allows specification flexibility
- Robust one-piece lead-frame design increases power-carrying capacity and efficiency, while providing improved durability
- Narrow connector allows high port density in a small area
- Will exceed IEEE 802.3bt standard up to 0.7 amps (140 watts) continuously
- Supports high-megabit and shared-sheath applications
- Available individually, in bulk packages of 25, and in bulk packages of 150 with a JackRapid™ Punchdown Tool

- IEEE 802.3bt PoE Type 1 (15.4 Watts) formerly 802.3af, Type 2 (30 Watts) formerly 802.3at, Type 3 (60 Watts), Type 4 (90 Watts)
- Cisco UPoE (60 Watts), UPoE+ (90 Watts)
- Power over HDBaseT™ PoH (95 Watts)
- UL 2043 Plenum Certified

SPECIFICATION SUBMITTAL

JOB NAME: <input style="width: 95%; height: 20px;" type="text"/>	CATALOG NUMBERS: <input style="width: 60%; height: 20px;" type="text"/> <input style="width: 35%; height: 20px;" type="text"/>	
JOB NUMBER: <input style="width: 95%; height: 20px;" type="text"/>	<input style="width: 60%; height: 20px;" type="text"/> <input style="width: 35%; height: 20px;" type="text"/>	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

