TECHNICAL SPECIFICATIONS

MODELS

The following table describes the NSM5200 model numbers. For example, the model number for a 12 TB, no expansion unit with a United Kingdom power cord is NSM5200-12-EUK.

Note: Models shipped to China do not include power cords. A CCC approved power cord must be used to power the equipment when used in China.

Model	Storage	Country Code
NSM5200 (no expansion) NSM5200F (fibre channel expansion)	12 TB	US = North America - EUK = Europe/United Kingdom
	24 TB	
	36 TB	
	48 TB	

SUPPLIED ACCESSORIES

Power Cord 2 power cords (based on country designation)

Note: Models shipped to China do not include power cords. A CCC approved power cord must be used to power the equipment when

used in China.

Rack Mount Kit Brackets, rails, and hardware

OPTIONAL ACCESSORIES

NSM5200-PS Replacement power supply module
NSM5200-FAN Replacement system fan (upper-middle)
NSM5200-FANB Replacement rear-chassis (rear panel) fan

NSM5200-FC Fibre channel expansion card

HD5200-2T-72K Replacement 2 TB hard drive and carrier HD5200-3000 Replacement 3 TB hard drive and carrier DS-EN-HDD-4TB Replacement 4 TB hard drive and carrier

OPTIONAL POWER ACCESSORIES

PWRCRD-S-AR	Standard power cord, Argentina
PWRCRD-S-AU	Standard power cord, Australia
PWRCRD-S-EU	Standard power cord, Europe
PWRCRD-S-UK	Standard power cord, United Kingdom
PWRCRD-S-US	Standard power cord, United States
PWRCRD-R-AR	Round power cord, Argentina
PWRCRD-R-AU	Round power cord, Australia
PWRCRD-R-EU	Round power cord, Europe
PWRCRD-R-UK	Round power cord, United Kingdom
PWRCRD-R-US	Round power cord, United States

SYSTEM

Operating System Linux RAID Level RAID 6

Effective Capacity

NSM5200-12 9.05 TB NSM5200-24 17.75 TB NSM5200-36 26.66 TB NSM5200-48 35.50 TB Drive Interface SAS/SATA II

Recommended PC Requirements

Web Browser Microsoft® Internet Explorer® 6.x (or later)

with Adobe® Flash® Player 10 (or later)

NETWORK

Interface 2, 1 Gbps Ethernet RJ-45 ports (1000Base-T)

Auxiliary Interfaces

USB 2.0 3 ports (2 rear, 1 front)