

LOCKS

ELECTROMAGNETIC LOCKS

LK-M12L



Surface-Mounted Magnetic Lock with holding force of 1200 pounds

LK-M06L



Surface-Mounted Magnetic Lock with holding force of 600 pounds

LK-M03



Surface-Mounted Magnetic Lock with holding force of 300 pounds

ELECTROMAGNETIC LOCKS ACCESSORIES

LA-L12 + LA-Z12



Adjustable L-Bracket for LK-M12L
L&Z Bracket for LK-M12L

LA-L06 + LA-Z06



Adjustable L-Bracket for LK-M06L
L&Z Bracket for LK-M06L

LA-L03 + LA-Z03



Adjustable L-Bracket for LK-M03
L&Z Bracket for LK-M03

LA-U12




U-Bracket for glass door for use with LK-M12L & LK-M06L

LA-U03



U-Bracket for glass door for LK-M03

ACCESS CONTROL



Maglock Specification	LK-M03	LK-M06L	LK-M12L
Voltage VDC	Dual Voltage 12/24 VDC		
Current	12 VDC: 360 mA 24 VDC: 180 mA	12 VDC: 500 mA 24 VDC: 250 mA	
Holding Force	136 kg (300 lb)	272 kg (600 lb)	544 kg (1200 lb)
Dimensions (L x W x D)	Main: 166 x 38.6 x 21.5 mm (6.5 x 1.5 x 0.8 in.) Contact: 129 x 31.5 x 7.5 mm (5.1 x 1.2 x 0.3 in.)	Main: 250 x 47.2 x 26.6 mm (9.8 x 1.9 x 1.0 in.) Contact: 185 x 37.5 x 11.5 mm (7.3 x 1.5 x 0.5 in.)	Main: 266 x 73 x 40 mm (10.5 x 2.9 x 1.6 in.) Contact: 184 x 60 x 16 mm (7.2 x 2.4 x 0.6 in.)
Weight	Main: 0.6 kg (1.4 lb) Contact: 0.3 kg (0.6 lb)	Main: 1.2 kg (2.7 lb) Contact: 0.7 kg (1.5 lb)	Main: 3.1 kg (6.8 lb) Contact: 1.4 kg (3.1 lb)

Brackets Specification	LA-L03	LA-L06	LA-L12	LA-Z03	LA-Z06	LA-Z12	LA-U03	LA-U12
Dimensions (L x W x D)	166 x 30 x 42 mm (6.5 x 1.2 x 1.7 in.)	250 x 30 x 48 mm (9.8 x 1.2 x 1.9 in.)	266 x 38 x 76 mm (10.5 x 1.5 x 3.0 in.)	166 x 38 x 38 mm (6.5 x 1.5 x 1.5 in.)	185 x 50 x 50 mm (7.3 x 2.0 x 2.0 in.)	185 x 63.8 x 63.8 mm (7.3 x 2.5 x 2.5 in.)	130 x 62 x 33.6 mm (5.1 x 2.4 x 1.3 in.)	185 x 62 x 33.6 mm (7.3 x 2.4 x 1.3 in.)
Weight	145 g (5.1 oz)	233 g (8.2 oz)	474 g (16.7 oz)	376 g (13.3 oz)	457 g (16.1 oz)	746 g (1.6 lb)	378 g (13.3 oz)	550 g (1.2 lb)