



2MP HD-TVI Intensifier® Turret Camera

HTINT60TM

2.8-12mm motorized lens, dark gray housing

HTINT601TA

3.6mm fixed lens, dark gray housing



Features

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator
- Built-in heater and anti-fog glass reduces condensation
- 3-axis for wall and ceiling mounting
- Additional 960H analog output

- Full OSD operation through on-board control and UTC (up the coax)
- Signal distance up to 1600 feet*
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- 12VDC & 24VAC dual voltage operation
- 5 year warranty
- NDAA Compliant*



| Camera Specifications | |
|-----------------------|------------------------------------|
| Image Sensor | 1/3" CMOS |
| Minimum Illumination | 0.001 lux (sense-up x32) |
| Effective Pixels | 1984 (H) x 1105 (V) |
| Total Pixels | 2000 (H) x 1121 (V) |
| Scanning System | Progressive |
| S/N Ratio | More than 50dB |
| Video Output | 1.0Vp-p / 75 Ohms |
| Electronic Shutter | Auto/Manual (1/30 - 1/30,000 sec.) |
| WDR | On (Low/Middle/High)/Off |
| Day/Night | Auto/Color/BW/External |
| White Balance | Auto/AWB/AWC-Set/Manual |
| Brightness | 0 - 20 (adjustable) |
| AGC | 0 - 10 (adjustable) |
| Sense-up | 2x - 32x (adjustable) |
| Backlight | BLC/HLC |
| Motion Detection | On/Off (4 zones) |
| Privacy Masking | On/Off (16 zones) |
| Mirror | On/Off |
| Flip | On/Off |
| Sharpness | 0 - 10 (adjustable) |
| DNR | Off/Low/Middle/High |
| Test Monitor Output | CVBS |
| Communication | UTC (up the coax) |

| Operating & Unit Specifications | |
|---------------------------------|--|
| Power | 12VDC/24VAC dual voltage (power supply included) |
| Power Consumption | 12VDC, 150mA max. 24VAC, 195mA max. |
| Operating Temperature | -4°F - 122°F |
| Unit Dimensions | 3.82" (H) x 5.47" (Dia) |
| Unit Weight | 1.54 lbs. |
| Certifications | FCC, RoHS |
| Signal Distance | Up to 1600 feet (depending on coax quality) |



*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessory



PSW5
12VDC
Power Supply



INTWM1
Wall Mount
(use with CVCJBD1)



INTCM1
Corner Mount
(use with INTWM1)



CVCJBD1
Junction Box