



2MP Ultra Intensifier® Bullet IP Camera with Junction Box

O2iB68

3.6mm fixed lens, dark gray housing



Features

- Next generation of Intensifier® technology provides an even more vivid color image in low light situations
- Preset image modes offer convenient settings for different environments
- Supports up to full HD 1080p resolution @ 30fps
- Built-in temperature and humidity sensor control automatic heater operation
- Built-in standard PoE (IEEE 802.3af)
- True WDR (wide dynamic range) operation
- Supports H.265, H.264 and MJPEG codecs
- IP68 compliant, weather resistant
- Junction box included for convenience
- Conformant with ONVIF Profile S
- 5 year warranty



Camera Specifications	
Image Sensor	Progressive scan 1/2.8" CMOS, 2M pixels
Effective Pixels	1945(H)x1097(V)
Field Of View	89° Horizontal, 47° Vertical
Maximum Resolution	1920x1080
Minimum Illumination	0.01 lux, f=0.94
White Balance	Auto/Presets
Compensation	WDR
Day/Night	Color
Electronic Shutter Speed	1/30 ~ 1/10000 sec
DNR	3D

Video Specifications	
Main Resolution	1920x1080 / 1280x720 @ 30fps
Compression	H.265 (v2 version), H.264 (HP/MP), MJPEG (sub stream)
Bitrate Control	VBR, CBR
Multiple Streaming	3 streams

Network Specifications	
Protocols	IPv4, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, DNS, NTP, SNMP
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP address filtering, digest authentication
User Access	Max. 8 simultaneous users Actual number of users may vary depending on bandwidth

Client Specifications	
Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS
Mobile	SecureGuard® Mobile (iPhone® and Android™)
Other Viewing Platforms	Apple TV and Amazon Fire TV
Embedded Recorder	Speco NVRs/Hybrids, ONVIF Profile S conformant recorders

Audio Specifications	
Mono Input	N/A
Mono Output	N/A

External Terminal Specifications	
Ethernet	10/100 Mbps
Power	DC jack

System Specifications	
PoE	Standard (IEEE 802.3af)
Alarm Triggers	Motion detection, sensor input
Alarm Events	FTP upload, email upload,
Image Settings	Privacy mask, Corridor mode

Operating & Unit Specifications	
Power	PoE, 12VDC (power supply not included)
Power Consumption	5W
Operating Temperature	-40°F to 140°F
Operating Humidity	0% - 90% relative humidity
Unit Dimensions	3" (W) x 3" (H) x 7.4" (D)
Unit Weight	1.2 lbs
Certifications	FCC, RoHS
Country of Origin	Made in Korea

NDAA COMPLIANT

*Products are in compliance with NDA Section 889 Part B Guidelines

Optional Accessories



POEINJ
12.95W
PoE Injector



PSW5
12VDC
Power Supply

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 9/13/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

speco technologies®