8MP (4K) IP Bullet Camera with Advanced Analytics, **NDAA Compliant**

08B8M

2.8-12mm motorized lens, white housing

Features

- Captures up to 8MP @ 30fps
- Up to 4x optical zoom
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 229' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB (card not included)
- ONVIF Profile T Compliant

Camera Specifications

• Line crossing, region intrusion, and video blurring detection

- Face/Human/Vehicle/Scene Change Detection*
- Two-way audio support
- IP67 Weather Resistance
- Junction box included
- (works with NPT/BSP specifications)
- 5 year warranty
- NDAA Compliant*



Chrome, Edge, Safari, Internet Explorer

SecureGuard® VMS, SecureGuard® CMS

IR 4K H.265 TRUE * ANALTICS SLOT POE TOCK

Cumera Spe	ciricarioris					
•		ogressive scan 1/2.8" CMOS, 8MP		Client Specifications		
Ū		340 x 2160 (8MP)		Web Browser Support		
Minimum Illumination		015lux @ F1.4, AGC ON; 0 lux with IR		PC Application		
Field of View (H)		l): 96° ~ 32°; (V): 64° ~ 18.4°; (D): 103.8° ~ 36.5°		Mobile		
Image Settings		igion of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynan efog, Sharpen, Noise Reduction, Corridor Mode (Image rotation)	nic,	Other Viewing Platforms		
Day/Night		nart IR with cut filter		System Specifications		
Compensation		Je WDR / BLC / HLC		PoE	S	Stando
Electronic Shutter Speed		sec. ~ 1/100000 sec.		Perimeter	Li	ine cr
DNR		DDNR		Protection	b	picycle
Angle Adjustment	Pe	ın 0° - 360°, Tilt 0° - 90°, Rotation 0°- 360°		Target Counting	Li	ine cr
Video Specif	ications			Exception Detection	S	Scene
Video Specifications				Face Detection	F	ace c
Main Stream Resolution		MP/6MP/5MP/4MP/2K/3MP/1080P/720P (1~30fps)		Alarm Triggers	Ν	Notio
Sub Stream Resolution		20P/D1/480 x 240 (1~30fps)		Image Settings Wate		Vater
Third Stream		D1/CIF/480x240 (1~30fps) 0perating & U		it S	nec	
Compression		H.265, H.264		Power		Pol
Bitrate Control		3R, CBR (64Kbps ~ 12Mbps)		Power Consumption		<12
Multiple Streaming	g 3	streams		Operating Temperature		-40
Network Specifications						
Protocols	UDP, DHCP,	NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1 x, UPnP, HTTP, HTTPs, Qo	S	1 0 ,		Les 3.9
DDNS support	Speco DDN	IS (free of charge)				
Security	User ID & Po	issword protection, IP/Mac address filtering, digest authentication	on	0		2.2 FC
User Access	Max. 10 simu	Itaneous users (Actual number of users may vary depending on bandwi	idth)	Certifications		FC
Interfaces				*with compatible Speco recon **Products are in compliance		IDAA
Network		RJ45 jack				
Power		DC jack		Cameras Inte	erfa	ices
Microphone Input		3.5mm		DC 12V RJ45 PoE		CVBS

SecureGuard[®] Client, Speco Blue (iPhone[®] and Android[™]) Apple TV[®], Amazon Fire TV[®] dard (IEEE 802.3af) crossing, region entrance/exiting/intrusion (human/vehicle/motorcycle/ le) detection crossing human/motor vehicle/motorcycle/bicycle e change video blur and video color cast detection detection and face capture on, Sensor Alarm, Analytics, SD card error ermark, IP address filtering, video mask, password protection cifications oE, 12VDC (power supply not included) 12W 0°F ~ 140°F (-40°C ~ 60°C) ess than 95 % (non-condensing) .93" (W) x 11.0" (D) x 3.5" (H); (100.3mm x 279.5mm x 88.9mm) .2 lbs. (1.0kg) CC, RoHS

A Section 889 Part B Guidelines



Network	RJ45 jack	SERIES COMPLIANT
Power	DC jack	Cameras Interfaces
Microphone Input	3.5mm	DC 12V RJ45 POE CVBS Audio In Audio Out Alarm In/Out
Audio Output	3.5mm	
Card Slot	MicroSD, up to 256GB (not included)	
Video Out	CVBS output (BNC x 1)	Optional Accessories
Alarm	1 CH alarm input; 1 CH alarm output	
Reset	Yes	
Audio Specifications		CLT3 CMT1 PMT1 WMT1 POEINJ PSW5
Audio Compression	G.711A / G.711U	Ceiling Mount Corner Mount Pole Mount Wall Mount 12.95W 12VDC PoE Injector Power Supply

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation

É App Store ▶ arrice ▶ arrive ▶ arrive

speco technologies