

**NEW**



# SWING GATE OPERATOR

1500LBS CAPACITY



**VIKING**  
ACCESS SYSTEMS™



RESIDENTIAL AND COMMERCIAL  
CLASS I, CLASS II, CLASS III AND CLASS IV VEHICULAR SWING GATE OPERATOR



**New "VFlex" Control Board**

- Diagnostics, Settings, and Status Display
- Conveniently Labeled Enclosure
- Ergonomically Located

**Multi-Layer Corrosion Protection**

- G90 Galvanized
- Clear Zinc Plating
- UV Rated Powder coating
- 1/4" Steel chassis

**Convenient Jbox for High Voltage Wiring**

**Battery Included: True Battery Back-up**



**Quick Release Handle for Manual Operation**

**Auxiliary Output for Additional Accessories While the Gate is in Motion**

**Conveniently Located Motor and Battery Reset Switches**

**Built-In Heater: Cold Weather Operation Down to -20°F**

**Removable Power Supply:**

- Convenient Fuse Access
- L.E.D. Status Indicators
- Convenient Power Switch
- E-Z Access Power Outlet
- E-Z Set-up 115V/230V
- Included Low Voltage Option



**COMPATIBLE WITH VIKING WIRELESS PRODUCTS**

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible handheld device.
- Plug & Play connection for the Viking wireless expansion products.



**BATTERY BACKUP INCLUDED**

- Standard Battery Backup provides 400 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.



**LIGHTNING PROTECTION**

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps.
- On board surge protection monitoring.



**PROTECTION**

- Multi-Layer Corrosion Protection
- G90 Galvanized
- Clear Zinc Plating
- UV Rated Powder coating
- 1/4" Steel Chassis



**INTEGRATED HEATER**

- Built-in heater for operating temperatures down to -20°F.
- This will allow you run your operator in the coldest conditions.



**SOLAR SMART**

- Power Saving technology minimizes current draw while at standby.



**DIAGNOSTICS DISPLAY**

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

Operational Voltage	...24 VDC 1/2HP
Main Power Source Options	...115 / 230 VAC Single Phase 24 AC/DC Solar Compatible
Battery	... 7 AmpHr 12 VDC x 2
Max Gate Capacity	...1500 lbs / 12' or 1000lbs / 16'
Operating Speed	...13-16 seconds per 90°
Battery Backup	...400 full continuous duty cycles (1500lbs)
Maximum Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 20° F to + 160° F

**WARRANTY:**  
**7 YEAR RESIDENTIAL**  
**5 YEAR COMMERCIAL**

- VIKING WIRELESS**
- SOLAR EFFICIENT OPERATION**



[www.vikingaccess.com](http://www.vikingaccess.com) • 800 908 0884