
Product Data Sheet | Anixter Catalog Page



Security/Alarm/Access Control/Sound Low-voltage Cable Non-Shielded Non-Plenum

Product Description

- FRPVC
- Bare Copper Conductor
- UL Listed Type CMR, CL3R



Applications

For use in security systems, intercom systems, sound/audio systems, access control, power-limited controls.

Specification

• CONDUCTOR: Bare copper

INSULATION: Polyvinyl Chloride (PVC)JACKET: Polyvinyl Chloride (PVC), Gray

STANDARDS: NEC: CMR (22-16 AWG), CL3R (14-12 AWG)

TEMPERATURE: 75°C

Standard color is gray, other colors available. Most items available on spools or boxes except on larger O.D. products. Diameters and weights may vary among manufacturers. Paired conductors also available

	Conductor	No. of				<u>Insulation</u>	Overall Jacket	Nom. O.D.	Approx. Wt.
Part No.	Size AWG	<u>Conductors</u>	<u>Voltage</u>	Rating	<u>Insulation</u>	Thickness (in.)	Thickness (in.)	<u>(in.)</u>	<u>lb./1,000 ft.</u>
AL-2202C-1-1N-09	22 (SOL)	2	300V	CMR	PVC	0.007	0.015	0.122	8
AL-2202C-2-1N-09	22	2	300V	CMR	PVC	0.007	0.015	0.120	11
AL-2203C-2-1N-09	22	3	300V	CMR	PVC	0.007	0.015	0.131	14
AL-2204C-2-1N-09	22	4	300V	CMR	PVC	0.007	0.015	0.142	16
AL-2204C-1-1N-09	22 (SOL)	4	300V	CMR	PVC	0.007	0.015	0.135	14
AL-2206C-2-1N-09	22	6	300V	CMR	PVC	0.007	0.015	0.170	24
AL-2208C-2-1N-09	22	8	300V	CMR	PVC	0.007	0.018	0.190	31
AL-2210C-2-1N-09	22	10	300V	CMR	PVC	0.007	0.020	0.210	39
AL-2212C-2-1N-09	22	12	300V	CMR	PVC	0.007	0.022	0.229	15
AL-2002C-2-1N-09	20	2	300V	CMR	PVC	0.008	0.015	0.148	21

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global supplier of communications and security products, electrical and electronic wire and cable, fasteners and other small components. We help our customers specify solutions and make informed purchasing decisions around technology, applications and relevant standards. Throughout the world, we provide innovative supply chain management solutions to reduce our customers' total cost of production and implementation.

Product Data Sheet | Anixter Catalog Page



Part No.	Conductor Size AWG	No. of Conductors	<u>Voltage</u>	Rating	Insulation	Insulation Thickness (in.)	Overall Jacket Thickness (in.)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
AL-2003C-2-1N-09	20	3	300V	CMR	PVC	0.010	0.015	0.161	26
AL-2004C-2-1N-09	20	4	300V	CMR	PVC	0.010	0.018	0.178	26
AL-1802C-2-1N-09	18	2	300V	CMR	PVC	0.009	0.015	0.172	16
AL-1803C-2-1N-09	18	3	300V	CMR	PVC	0.009	0.015	0.187	30
AL-1804C-2-1N-09	18	4	300V	CMR	PVC	0.009	0.018	0.203	37
AL-1806C-2-1N-09	18	6	300V	CMR	PVC	0.009	0.020	0.226	52
AL-1808C-2-1N-09	18	8	300V	CMR	PVC	0.009	0.020	0.242	66
AL-1602C-2-1N-09	16	2	300V	CMR	PVC	0.009	0.018	0.198	30
AL-1604C-2-1N-09	16	4	300V	CMR	PVC	0.009	0.020	0.234	54
AL-1402C-2-1N-09	14	2	300V	CL3R	PVC	0.010	0.025	0.238	45
AL-1404C-2-1N-09	14	4	300V	CL3R	PVC	0.010	0.025	0.286	74
AL-1202C-2-1N-09	12	2	300V	CL3R	PVC	0.011	0.028	0.296	68

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com