



# P610 ADVANCED IP67 STAINLESS STEEL INDUSTRIAL WEIGHING INDICATOR



## GENERAL FEATURES

- Wide angle LCD display with multi-coloured back light, 22mm main digits and 8mm alphanumeric auxiliary digits.
- Desk, wall and panel mount versions
- Up to 999999d display resolution
- Up to 800 conversions per second
- OIML approved to 10000d
- Dedicated navigation keys provide easy operation
- High sensitivity (to 0.05  $\mu$ V/d)
- Linearity correction
- Gravity Adjustment
- Keypad locking
- Mains and 12-28V DC versions
- Dynamic weighing
- Up to 8x 350 $\Omega$  load cells
- 2x RS-232C 1x USB and 1x RS485 data port standard
- Connectivity to remote displays and printers
- Programmable print format
- Choice of 6 languages for printing
- Built in real time clock
- User setable password access
- Stainless steel housing to IP67

## BASIC WEIGHING

- Multiple tare
- Auto tare

## APPLICATIONS

- Process and industrial weighing (silos, tanks, hoppers, etc.)
- Food processing and hygienic applications
- Label printing with barcode
- General harsh conditions weighing
- Livestock and dynamic weighing

## SYSTEM INTEGRATION

- Fieldbus connectivity (optional) with Profibus, Profinet, CANopen, Ethernet TCP/IP, EtherNet/IP, EtherCAT, CC-Link, Powerlink Modbus RTU / TCP and Analogue outputs
- 9 different types of output (dependant on selected application) are configurable with optional Digital I/O

### ... Azure Signature Series!

The PT610 is an advanced, high quality general purpose weighing indicator for industry in a durable IP67 stainless steel housing. Ideal for platform, truck and hopper scales among other applications and is available with a wide range of options.

The PT610 is approved by Weights & Measures Authorities for use in Accuracy Class III applications with 10000 intervals in accordance with OIML R76.

Weighing, and Dynamic weighing for animals and fluctuating loads are standard as is printing which is selectable from 6 languages.

A wide range of options is available for integration by Fieldbus connectivity, desk, wall or panel mounting and digital I/O.

Easy, practical operation via navigation keys with 6 large 22mm digits, 16 alphanumeric characters 8mm high and wide viewing angle, multi-colour backlit LCD display.

The PT610 is powered by AC power with integral mains cable. A version is available for powering from 12-28VDC



Accupoint weigh module



ESTABLISHED  
IN  
1979



PT Limited

2/7 Marken Place, Glenfield, Auckland 0627, New Zealand  
PO Box 102041 NSMC, Auckland 0745. Ph.+64 9 444 4312

[www.ptglobal.com](http://www.ptglobal.com)



## PT610 SPECIFICATIONS

ACCURACY	OIML R76 Class III 10000. Single range, multi-range, multi-interval operation
DISPLAY	Wide view backlit LCD with 22mm digit height, 8mm alphanumerics and 3 back light colours
RESOLUTION	Max. Displayed 999999 divn., internal 16000000, 24 bit Delta Sigma ADC, up to 800 conv/s
CAPACITY & UNITS DISPLAY	Up to 300 000kg, Units g, kg, oz, lb Metric/Imperial switchable
DISPLAY ANNUNCIATORS	Gross, net, motion, centre of zero, units
KEYPAD	11 key (on/off, Tare/Clear, Zero, unit swap, 10x resolution, navigation and print)
EXCITATION	5VDC 125mA, up to 8x 350Ω or 16x 700Ω load cells, 4 or 6 wire, maximum 1000 m/mm <sup>2</sup>
INPUT VOLTAGE RANGE AND SENSITIVITY	-5mV to +19mV. Minimum 0.05 μV/division (0.4 μV/division approved)
ZERO ADJUSTMENT INPUT RANGE	-5mV to +19mV
OPERATING ENVIRONMENT	-15°C to +55°C; max. 90% RH (80% RH, -10~40°C approved), non-condensing. IP67 sealing.
ENCLOSURE AND DIMENSIONS	Stainless steel, IP67 protected. Wall type: 260x200x65, Desk type: 250x180x85, weight 2.3kg
POWER SUPPLY	Integral cable, 100-240 VAC (100-125VAC with USA plug), 50-60 Hz. 12VDC (12-28) configurable.

## FEATURES

CALIBRATION	Calibration can be performed with or without load cell non-linearity correction. Calibration with test weights, Electronic calibration without test weights, Temporary zero calibration, Zero adjustment, Gain adjustment
DIGITAL FILTER	Adaptive digital filter adjustable in 5 steps for standard weighing, Programmable dynamic (animal) weighing filter.
WEIGHING FUNCTIONS	Taring, zeroing, auto zero tracking, motion detection, auto zero at power up, tare status save at power off, increased resolution, automatic tare and clear, temporary gross indication, unit change.
STANDARD APPLICATIONS	Labelling, relay setpoints, functional digital outputs, livestock weighing, fieldbus interfacing and high resolution scales.
APPLICATION MEMORY	Standard Memory to save limit values of your industrial weighing. Memory size is 500 item records.
DYNAMIC (ANIMAL WEIGHING)	Supported by smart dynamic weighing algorithms

## COMMUNICATION

RS-232C	2x 3 wire ports. Opto-isolated. 1200 to 57600 baud, 7/8-E/O/N-1.
RS-485	1200 to 57600 baud, 7/8-E/O/N-1. Up to 31 stations.
USB	Standard USB for Mini-B cable (internal on PCB).
FIELDBUS (option required)	Modbus, Profibus, Profinet, Ethernet TCP/IP, CANopen, EtherNET/IP, EtherCAT, CC-Link, Powerlink.
DATA OUTPUT	Demand (BSI), Continuous and Fast Continuous, Fieldbus (option dependent).

## PRINTING/WEIGH TICKET

TICKET FORMAT	Programmable for different weighing modes. Format may include Date, Time, Ticket No, Gross, Tare and Net weights. Ticket weighing number can be Preset.
DATE FORMAT	Programmable as dd.mm.yyyy, mm.dd.yyyy or yyyy.mm.dd
PRINT LANGUAGES	English, German, French, Italian, Spanish, Turkish



ESTABLISHED  
IN  
1979



PT Limited

2/7 Marken Place, Glenfield, Auckland 0627, New Zealand  
PO Box 102041 NSMC, Auckland 0745. Ph.+64 9 444 4312

[www.ptglobal.com](http://www.ptglobal.com)



## MODELS AVAILABLE

Model	Features	Part Numbers
PT610DM	Standard PT610 Desk Mount – The desk mount has a sloping panel, will also wall mount with cables at the rear.	EP610DM00USXXX, EP610DM00UKXXX, EP610DM00EUXXX, EP610DM00AUXXX
PT610WM	Standard PT610 Wall Mount – The wall mount has a flat panel with cables exiting in the front.	EP610WM00USXXX, EP610WM00UKXXX, EP610WM00EUXXX, EP610WM00AUXXX
PT610PM	Standard PT610 Panel Mount	EP610PM00USXXX, EP610PM00UKXXX, EP610PM00EUXXX, EP610PM00AUXXX

## Options\*\*

MOUNTING	Column mount kit, Wall mount kit, 2D Swivelling wall mount kit
ALIBI MEMORY	999999 records
MODBUS (RTU)	(Software option on SD Card)
DIGITAL INPUT/OUTPUT	Optoisolated 4 digital input, 12 to 28 VDC, 10mA / 5 relay contacts, 250 VAC or 30 VDC, 0.2A
ANALOGUE OUTPUT*	0-5 VDC, 0-10 VDC, >10 k $\Omega$ / 4-20mA, 0-20mA, <500 $\Omega$ . 60000 steps, up to 300m.
FIELDBUS* (each a separate option)	Profibus, Profinet, Ethernet TCP/IP (incl. Modbus,TCP), CANopen, EtherNET/IP, EtherCAT, CC-Link, Powerlink.

\* Only one option of Fieldbus or Analogue output can be fitted per indicator.

\*\*The full range of available options are listed on the PT web site.



ESTABLISHED  
IN  
1979



PT Limited

2/7 Marken Place, Glenfield, Auckland 0627, New Zealand  
PO Box 102041 NSMC, Auckland 0745. Ph.+64 9 444 4312

[www.ptglobal.com](http://www.ptglobal.com)



Features\Models	Desk Mount	PT610DM	PT620DM	PT630DM				
	Wall Mount	PT610WM	PT620WM	PT630WM				
	Panel Mount	PT610PM	PT620PM	PT630PM				
Touch Free IR Keys (2 Keys)	n/a	n/a	Yes					
Ethernet (TCP/IP) interface	0 <sup>1</sup>	n/a						
Modbus (RTU /TCP)	0	n/a	0					
PROFIBUS DPV1 interface + 4 Input/5 Relay Output	0 <sup>1</sup>	n/a	0 <sup>1</sup>					
PROFINET interface + 4 Input/5 Relay Output								
Ethernet/IP interface + 4 Input/5 Relay Output								
CANopen interface + 4 Input/5 Relay Output								
EtherCAT interface + 4 Input/5 Relay Output								
CC-Link interface + 4 Input/5 Relay Output								
Powerlink interface + 4 Input/5 Relay Output								
2 Platform weighing	n/a	n/a	0					
BSI data interface (BSI-PRO command set)	n/a		Yes					
Classifying by weight								
Check-weighing								
Filling								
Dynamic/Animal weighing								
Piece Counting								
Weight Totalling								
Piece Totalling								
Pre-Tare entry								
Pre-Tare value storage (500 values)								
ID data (ID1, 500 records for stored items)								
ID Data (ID2, second set 500 records)								
Average Piece Weight storage for counting (500 values)								
Alibi Memory (999999 records)					0			
Dynamic/Unstable load weighing					Yes			
Setpoint storage (500 sets)								
Unit selection (g, kg, t, lb, oz)								
Unit Switching (kg/lb, g/oz)								

0 = Option. 0<sup>1</sup> = Only one Option can be installed at a time.

Features\Models	Desk Mount	PT610DM	PT620DM	PT630DM				
	Wall Mount	PT610WM	PT620WM	PT630WM				
	Panel Mount	PT610PM	PT620PM	PT630PM				
Docket Printing	Yes							
Label Printing (with Barcode <sup>2</sup> )								
Auto-zero tracking and auto-zero at power-up								
Motion detection								
Adaptive digital filter for faster measuring								
Electronic calibration (vCal) without test weights								
Electronic calibration (vCal) over field bus								
Zeroing and Taring via fieldbus								
Zero and Span calibrations over field bus								
Zero adjustment without span change								
Span adjustment with test weights								
Span adjustment without unloading the scale								
3 point calibration (linearity correction)								
Programming by PT AzCom PC software								
8 load cells 350 Ω or 16 load cells 700 Ω								
100 – 240 VAC								
12 to 28 VDC power supply range								
1 000 to 999 999 display resolution								
High internal resolution up to 16 000 000 counts								
Up to 800 conversion per second								
RS-232C Serial interface								
RS-232C Second Serial interface								
RS-485 Serial interface								
USB Serial Interface								
BSI data interface (BSI-BASE command set)								
Continuous data output								
Fast Continuous data output								
4 Digital Inputs, 5 relay outputs (DI/O)					0 <sup>1</sup>			
Analogue output (4–20, 0–20mA, 0–5, 0–10VDC)+DI/O								
2 = Third party barcode software required. n/a = Not Available								



ESTABLISHED  
IN  
1979



PT Limited  
2/7 Marken Place, Glenfield, Auckland 0627, New Zealand  
PO Box 102041 NSMC, Auckland 0745. Ph.+64 9 444 4312  
[www.ptglobal.com](http://www.ptglobal.com)

